

Camera Link

High Flex Camera Link with 38999 Mil-Spec connector

Product Outline

Designed specifically for extremely rugged conditions, these durable assemblies utilize military grade connectors along with our High Flex cable to provide the ultimate in dependability, electrical and mechanical performance.

These assemblies are fully customizable to support one or more cameras by utilizing any combination of our four Camera Link bulk cables along with multiple options of overmolds for both standard and Mini Camera Link connectors.



Main Product Specifications

Features

- Military grade 38999 connector
- High Flex cable designed to surpass 5 million flexes
- RoHS Compliant
- IP 67 capable 38999 connector

Application Examples

- Isolation Chambers
- Single disconnect for multiple cameras
- Rail inspection
- Unmanned Aerial Vehicles (UAV's)

Cable Specifications

Overall Diameter	.375 Inches or .270 Inches
Max Temperature	80 Degrees C
Jacket Color	Black
UL/CSA Rated	Yes
Min. Bend Radius	3.75 Inches or 2.70 Inches

Primary Components

Cable	11 Individually Shielded Twisted Pairs
Connector A	38999 military grade
Connector B	26 Pos MDR or SDR (HDR)

Ordering Information

Order Number	Description
Contact customer service for custom part number	38999 High Flex Camera Link Assembly



Pyramid Imaging
4951 Adamo Dr. Suite 224
Tampa, FL 33605-5919
Phone: 813.984.0125 Fax: 866.874.9521
www.pyramidimaging.com

