



1/2" 1.4/4.5mm C-Mount		1/3"	
Focal Length		f=4.5mm±5%	
Max. Diameter (Ratio)		F=1 : 1.4±5%	
Element		6 Group 7 Elements	
Picture Size		4.8x6.4mm	3.6x4.8
Angle	Ver.	59.4°	45.1°
	Hor.	79.0°	59.7°
	Dia.	98.2°	74.5°
Distortion (TV)		-17.5%	
Shooting Range at M.O.D/	Ver.	180mm	
	Hor.	260mm	
	Dia.	364mm	
Minimum Object Distance		0.2m	
Flange back		17.526 mm in air	
Back Focus		9.96mm in air	
Filter screw size		M30.5x0.5	
Front/Rear Effective Dia.		F: φ 15.1mm	R. φ 10.1mm
Mount		C-MOUNT	
Exit Pupil		-17.5mm	
Temperature Range		-10~+45° C	
Storage Temperature Range		-40~+60° C	
Resolution		Center 100 LP/mm	Corner 40LP/mm
Stopper Strength		10kgf · cm	
Endurance Tests		Iris: 5,000Times	Focus: 5,000Times
Operating Torque		Iris: 50~600gf · cm	Focus: 100~1000gf · cm
Weight		54g±5g	

LM5NCR