



1/2" 1.4/6mm C		1/3"
Focal Length	f=6mm±5%	
Max. Diameter (Ratio)	F=1 : 1.4±5%	
Element	6 Group 7 Elements	
Picture Size	4.8x6.4mm	3.6x4.8
Angle	Ver.	44.0°
	Hor.	57.3°
	Dia.	69.4°
Distortion (TV)	-1.0%	
Shooting Range at M. O. D.	Ver.	128mm
	Hor.	174mm
	Dia.	221mm
Minimum Object Distance	0.2m	
Flange Back	17.526mm in air	
Back Focus	9.46mm in air	
Filter Screw Size	M25.5x0.5	
Front/Rear Effective Dia.	F: φ 16.2mm	R: φ 8.7mm
Mount	C-MOUNT	
Exit Pupil	-77.3mm	
Temperature Range	-10~+45° C	
Storage Temperature Range	-40~+60° C	
Resolution	Center: 100LP/mm	Corner: 60LP/mm
Stopper Strength	10kgf · cm	
Endurance Tests	Iris: 5,000Times	Focus: 5,000Times
Operating Torque	Iris: 50~600gf · cm	Focus: 100~1000gf · cm
Weight	60g±5g	

1/2" 1.4/6mm

LM6NCL