



<b>1/2" 1.4/ 6 mm C</b>		<b>1/3"</b>	
Focal Length		f=6mm±5%	
Max. Diameter (Ratio)		F=1 : 1.4±5%	
Element		6 Group 7 Elements	
Picture Size		4.8x6.4mm	3.6x4.8
Angle	Ver.	44.0°	33.7°
	Hor.	57.3°	44.2°
	Dia.	69.4°	54.4°
Distortion (TV)		-1.0%	
Shooting Range at M.O.D.	Ver.	128mm	
	Hor.	174mm	
	Dia.	221mm	
Minimum Object Distance		0.2m	
Flange Back		12.5 mm in air	
Back Focus		9.46mm in air	
Filter Screw Size		M30.5x0.5	
Front/Rear Effective Dia.		F: φ 16.2mm	R: φ 8.7mm
Mount		C-MOUNT	
Exit Pupil		-77.3mm	
Temperature Range		-10~+45° C	
Storage Temperature Range		-40~+60° C	
Resolution		Center: 100 LP/mm	Corner: 40LP/mm
Stopper strength		10kgf ▪ cm	
Endurance Tests		Iris: 5,000Times	Focus: 5,000Times
Operating Torque		Iris: 50~600gf ▪ cm	Focus: 100~1000gf ▪ cm
Weight		63g±5g	

LM6NCR