



1/3" 1.4/1.6~3.4mm CS

| | | |
|---------------------------|-------------------|---------------------------|
| FOCAL LENGTH | f=1.6~3.4mm | |
| MAX. DIAMETER (RATIO) | F=1:1.4~16~CLOSE | |
| PICTURE SIZE | 3.6x4.8mm 1/3" | |
| ANGLE OF VIEW | VER. | 114.1° ~55.8° |
| | HOR. | 180° ~84.3° |
| | DIA. | 180° ~106.1° |
| MINIMUM FOCUS DISTANCE | 0.2m | |
| FLANGE BACK | 12.5mm | in air |
| BACK FOCUS | 7.07mm~11.55mm | in air |
| FILTER SCREW SIZE | — | |
| FRONT/REAR EFFECTIVE DIA. | φ 27.8mm | φ 8.6mm |
| MOUNT | CS-MOUNT | |
| EXIT PUPIL | 85.5mm | |
| TEMPERATURE RANGE | -10~45 C° | |
| STORAGE TEMPERATURE RANGE | -40~60 C° | |
| RESOLUTION | 100lp/mm (Center) | 40lp/mm (Corner) |
| STOPPER STRENGTH | 10kgf/cm | |
| ENDURANCE TESTS | F:5,000Times | Z:5,000Times I:5,000Times |
| WEIGHT | 98g | |

| | | | | |
|---------|--|--------------------|--|--|
| | | 1/1 | | |
| | | 1/3" 1.4/1.6~3.4mm | | |
| | | LMVZ164 | | |
| 98.11.7 | | | | |