



1/3" 1.4/2.5~6mm CS

FOCAL LENGTH	f=2.5~6mm	
MAX. DIAMETER (RATIO)	F=1:1.4~16~CLOSE	
ELEMENT	6GROUP 7ELEMENTS (1ASP.)	
PICTURE SIZE	3.6x4.8mm 1/3"	
ANGLE OF VIEW	VER.	80.9 ° ~34.2 °
	HOR.	107.6 ° ~45.6 °
	DIA.	133.3 ° ~56.8 °
DISTORTION	-19.4%~-2.5%	
SHOOTING RANGE AT MINIMUM FOCUS DISTANCE	VER.	364mm~131mm
	HOR.	584mm~179mm
	DIA.	995mm~230mm
MINIMUM FOCUS DISTANCE	0.2m	
FLANGE BACK	12.5mm	in air
BACK FOCUS	8.72mm~14.24mm	in air
FILTER SCREW SIZE	—	
FRONT/REAR EFFECTIVE DIA.	φ 27.6mm	φ 7.4mm
MOUNT	CS-MOUNT	
EXIT PUPIL	W18583~T-30mm	
TEMPERATURE RANGE	-10~45 C°	
STORAGE TEMPERATURE RANGE	-40~60 C°	
RESOLUTION	100lp/mm (Center)	40lp/mm (Corner)
STOPPER STRENGTH	10kgf/cm	
ENDURANCE TESTS	F:5,000Times	Z:5,000Times I:5,000Times
WEIGHT	83g	

		1/1	
		1/3" 1.4/2.5~6mm	
		LMVZ256	
96.8.19			