


CF12.5HA-1

FIXED




Unit: mm





- High-resolution design, providing support for up to 1.5 megapixel camera resolution.
- Rear focusing system provides improved performance in macro photography.
- Wide-aperture (F1.4) design achieves clear images under low light intensity.
- Low-distortion design achieving accurate image input.
- Robust enclosure resistant to vibrations and shocks. Equipped with locking knobs for the iris and the focus.



MANUAL


| Focal Length (mm) | | 12.5 |
|--|-------|-----------------|
| Iris Range | | F1.4 ~ F22 |
| Operation | Focus | Manual |
| | Iris | Manual |
| Angle Of View (H×V) | 1" | 54°13′ × 42°01′ |
| | 2/3" | 38°47′ × 29°35′ |
| | 1/2" | 28°43′ × 21°44′ |
| Focusing Range (From Front Of The Lens) (m) | | ∞ ~ 0.1 |
| Object Dimensions at M.O.D. (HXV) (mm) | 1" | 120 × 90 |
| | 2/3" | 83 × 62 |
| | 1/2" | 60 × 45 |
| Back Focal Distance (in air) (mm) | | 16.07 |
| Exit Pupil Position (From Image Plane) (mm) | | -101 |
| Filter Thread (mm) | | M49 × 0.75 |
| Mount | | С |
| Mass (g) | | 290 |
| · | | |

Remarks

- · With Metal Mount
- With Locking Knob for Iris and Focus




CF16HA-1







- High-resolution design, providing support for up to 1.5 megapixel camera resolution.
- Rear focusing system provides improved performance in macro photography.
- Wide-aperture (F1.4) design achieves clear images under low light intensity.
- Low-distortion design achieving accurate image input.
- Robust enclosure resistant to vibrations and shocks. Equipped with locking knobs for the iris and the focus.



| Focal Length (mm) | | 16 | |
|---|-------|-----------------|-------|
| Iris Range | | F1.4 ~ F22 | |
| Operation | Focus | Manual | |
| | Iris | Manual | |
| Angle Of View (H×V) | 1" | 43°36′ × 33°24′ | |
| | 2/3" | 30°45′ × 23°18′ | |
| | 1/2" | 22°37′ × 17°04′ | |
| Focusing Range (From Front Of The Lens) (m) | | ∞ ~ 0.1 | |
| Object Dimensions | 1" | 100 × 75 | |
| at M.O.D. | 2/3" | 69 × 51 | |
| (H×V) (mm) | 1/2" | 50 × 37 | |
| Back Focal Distance (in air) (mm) | | 17.99 | |
| Exit Pupil Position (From Image Plane) (mm) | | -172 | PV |
| Filter Thread (mm) | | M49 × 0.75 | ' y |
| Mount | | C | 45 Ea |
| Mass (g) | | 280 | S |

Remarks • With Me

- · With Metal Mount
- With Locking Knob for Iris and Focus

Pyramid Imaging

45 East 11th Avenue Tampa, FL 33605 sales@pyramidimaging.com www.pyramidimaging.com 813-786-3785