



1/2"		1.4/3.5mm	C	1/3"
Focal Length		f=3.5mm±5%		
Max. Diameter (Ratio)		F=1 : 1.4±5%		
Element		6 Group 7 Elements		
Picture Size		4.8x6.4mm		3.6x4.8
Angle	Ver.	76.6°		57.7°
	Hor.	103.6°		77.0°
	Dia.	132.1°		97.5°
Distortion (TV)		-28.0%		
Shooting Range at M.O.D.	Ver.	247mm		
	Hor.	396mm		
	Dia.	688mm		
Minimum Object Distance		0.2m		
Flange Back		17.526 mm in air		
Back Focus		8.89mm in air		
Filter Screw Size				
Front/Rear Effective Dia.		F: $\phi 19.6$ mm		R: $\phi 10.4$ mm
Mount		C-MOUNT		
Exit Pupil		-71.4mm		
Temperature Range		-10~+45° C		
Storage Temperature Range		-40~+60° C		
Resolution		Center: 100LP/mm		Corner: 60LP/mm
Stopper Strength		10kgf · cm		
Endurance Tests		Iris: 5,000Times		Focus: 5,000Times
Operating Torque		Iris: 50~600gf · cm		Focus: 100~1000gf · cm
Weight		73g±5g		

1/2" 1.4/3.5mm

LM4NCL