



1" 1.4/50mm C		1"	2/3"	1/1.8"
FOCAL LENGTH		f=50mm		
MAX. DIAMETER (RATIO)		F=1:1.4~16		
PICTURE SIZE		9.6x12.8mm	6.6x8.8mm	5.4x7.2mm
ANGLE	VER. ANGLE	10.8°	7.5°	6.2°
	HOR. ANGLE	14.5°	10.0°	8.2°
	DIA. ANGLE	18.0°	12.5°	10.2°
DISTORTION (TV)		0.05%		
SHOOTING RANGE AT MINIMUM FOCUS DISTANCE	VER.	91.3mm	62.9mm	51.4mm
	HOR.	121.8mm	83.8mm	68.6mm
	DIA.	152.9mm	104.8mm	85.7mm
MINIMUM FOCUS DISTANCE		0.5m		
FLANGE BACK		17.526mm in air		
BACK FOCUS		14.8mm in air		
FILTER SCREW SIZE		M40.5x0.5		
FRONT/REAR EFFECTIVE DIA.		FRONT φ35.0mm		REAR φ15.5mm
MOUNT		C-MOUNT		
EXIT PUPIL		-44.4mm		
TEMPERATURE RANGE		-10~+50°C		
STORAGE TEMPERATURE RANGE		-20~+60°C		
RESOLUTION CENTER/CORNER		CENTER 120lp/mm		CORNER 80lp/mm
WEIGHT		210 g		

NOTE: Specifications and availability are subject to change without notice



**Pyramid Imaging**

945 East 11th Avenue Tampa, FL 33605  
 sales@pyramidimaging.com  
 www.pyramidimaging.com  
 813-786-3785

		1/1	HR980SW
		1" F1.4 f=50mm	
2015.7.30			
2014.12.25			
2013.4.15		LM50HC-SW	