



1" 1.4/25mm C		1"	2/3"	1/1.8"
FOCAL LENGTH		f=25mm		
MAX. DIAMETER (RATIO)		F=1:1.4~16		
PICTURE SIZE		9.6x12.8mm	6.6x8.8mm	5.4x7.2mm
ANGLE	VER. ANGLE	22.0°	15.1°	12.4°
	HOR. ANGLE	29.3°	20.2°	16.5°
	DIA. ANGLE	36.6°	25.2°	20.6°
DISTORTION (TV)		-1.0%		
SHOOTING RANGE AT	VER.	119.2mm	81.4mm	66.5mm
	HOR.	160.7mm	109.1mm	88.9mm
	DIA.	204.3mm	137.4mm	111.7mm
MINIMUM FOCUS DISTANCE		0.3m		
FLANGE BACK		17.526mm in air		
BACK FOCUS		16.5mm in air		
FILTER SCREW SIZE		M35.5x0.5		
FRONT/REAR EFFECTIVE DIA.		FRONT ϕ 21.0mm		REAR ϕ 19.4mm
MOUNT		C-MOUNT		
EXIT PUPIL		-57.9mm		
TEMPERATURE RANGE		-10~+50°C		
STORAGE TEMPERATURE RANGE		-20~+60°C		
RESOLUTION CENTER/CORNER		CENTER 120lp/mm		CORNER 80lp/mm
WEIGHT		135 g		

NOTE: Specifications and availability are subject to change without notice

Pyramid Imaging Inc • 945 East 11th Avenue • Tampa, FL 33605 • +1 813 984 0125 • sales@pyramidimaging.com • pyramidimaging.com



		1/1	HR978SW
		1" F1.4 f=25mm	
2015.7.30		LM25HC-SW	
2014.12.25			
2013.4.15			