



φ23 2.0/50mm C	
FOCAL LENGTH	f=50mm
MAX. DIAMETER (RATIO)	F=1:2.0~22
ELEMENT	6 GROUPS 7 ELEMENTS
PICTURE SIZE	13.8x18.4mm
ANGLE	VER. ANGLE 15.7°
	HOR. ANGLE 20.6°
	DIA. ANGLE 25.4°
DISTORTION (TV)	0.8%
SHOOTING RANGE AT	VER. 75mm
MINIMUM FOCUS	HOR. 100mm
DISTANCE	DIA. 124mm
MINIMUM FOCUS DISTANCE	0.3m
FLANGE BACK	17.526mm in air
BACK FOCUS	21.6mm in air
FILTER SCREW SIZE	M37.5x0.5
FRONT/REAR EFFECTIVE DIA.	FRONT φ31.8mm REAR φ16.0mm
MOUNT	C-MOUNT
EXIT PUPIL	-19.1mm
TEMPERATURE RANGE	-10~+50°C
STORAGE TEMPERATURE RANGE	-20~+60°C
RESOLUTION CENTER/CORNER	CENTER 160本/mm CORNER 80本/mm
LENS COATING	WIDE BAND MULTI COATING
WEIGHT	220 g

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



Pyramid Imaging

945 East 11th Avenue Tampa, FL 33605
 sales@pyramidimaging.com
 www.pyramidimaging.com
 813-786-3785

		尺度 1/1	承認 八木	製 富永 図 富永
		機種名	φ23 F2.0 f=50mm	
		機種番	LM50XC	
2010.06.01	作成年月日			