



Φ23 2.0/25mm C		
FOCAL LENGTH		f=25mm
MAX. DIAMETER (RATIO)		F=1:2.0~16
ELEMENT		6 GROUPS 8 ELEMENTS
PICTURE SIZE		13.8x18.4mm
ANGLE	VER. ANGLE	31.1°
	HOR. ANGLE	40.9°
	DIA. ANGLE	50.2°
DISTORTION (TV)		-0.57%
SHOOTING RANGE AT	VER.	93mm
MINIMUM FOCUS	HOR.	125mm
DISTANCE	DIA.	157mm
MINIMUM FOCUS DISTANCE		0.15m
FLANGE BACK		17.526mm in air
BACK FOCUS		24.3mm in air
FILTER SCREW SIZE		M40.5x0.5
FRONT/REAR EFFECTIVE DIA.		FRONT Φ31.4mm REAR Φ18.2mm
MOUNT		C-MOUNT
EXIT PUPIL		-63.9mm
TEMPERATURE RANGE		-10~+50° C
STORAGE TEMPERATURE RANGE		-20~+60° C
RESOLUTION CENTER/CORNER		CENTER 160本/mm CORNER 80本/mm
LENS COATING		WIDE BAND MULTI COATING
WEIGHT		250 g

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。

		尺度 1/1	承認 八木	製 富永 図
		機種名 Φ23 F2.0 f=25mm		
		機種番 LM25XC		
2010.06.03	作成年月日			



Pyramid Imaging

945 East 11th Avenue Tampa, FL 33605
 sales@pyramidimaging.com
 www.pyramidimaging.com
 813-786-3785