



$\phi 23$ 2.0/16mm C		
FOCAL LENGTH		$f=16$ mm
MAX. DIAMETER (RATIO)		F=1:2.0~22
ELEMENT		9 GROUPS 11 ELEMENTS
PICTURE SIZE		13.8x18.4mm
ANGLE	VER. ANGLE	47.2°
	HOR. ANGLE	60.6°
	DIA. ANGLE	72.0°
DISTORTION (TV)		0.02%
SHOOTING RANGE AT MINIMUM FOCUS	VER.	101 mm
	HOR.	135 mm
DISTANCE	DIA.	168 mm
MINIMUM FOCUS DISTANCE		0.1m
FLANGE BACK		17.526mm in air
BACK FOCUS		13.0mm in air
FILTER SCREW SIZE		M40.5x0.5
FRONT/REAR EFFECTIVE DIA.		FRONT $\phi 31.2$ mm REAR $\phi 16.5$ mm
MOUNT		C-MOUNT
EXIT PUPIL		-26.2mm
TEMPERATURE RANGE		-10~+50° C
STORAGE TEMPERATURE RANGE		-20~+60° C
RESOLUTION CENTER/CORNER		CENTER 160本/mm CORNER 80本/mm
LENS COATING		WIDE BAND MULTI COATING
WEIGHT		250 g

NOTE: Specifications and availability are subject to change without notice  
 注) 本仕様については、予告なしに変更する場合があります。



Pyramid Imaging

945 East 11th Avenue Tampa, FL 33605  
 sales@pyramidimaging.com  
 www.pyramidimaging.com  
 813-786-3785

	尺度 1/1	承認 八木	製 富永 図 富永
	機種名 $\phi 23$ F2.0 $f=16$ mm		
	機種番 LM16XC		
2010.06.03	作成年月日		