



### SPECIFICATIONS

### AUTO IRIS

### W/O CIRCUIT

1. USE	FOR 1/3" B/W COLOR CAMERA		
2. FOCAL LENGTH	5~40mm		
3. ZOOM RATIO	8 x		
4. MAX. DIA. RATIO	F1.6		
5. IRIS RANGE	F1.6-360		
6. IMAGE SIZE	φ 6		
7. BACK FOCAL LENGTH	W 9.6	T 15.9	in air
8. FLANGE FOCAL LENGTH	12.5 mm		in air
9. FOCUS RANGE	W 0.1m	T 1m	
10. FIELD ANGLE	DIA.	W 66.9 °	T 8.8 °
	HOR.	53.6 °	6.5 °
	VER.	40.2 °	4.8 °
11. FIELD OF VIEW AT M. O. D.	DIA.	W 162.0 mm	T 177.0 mm
	HOR.	123.8 mm	130.0 mm
	VER.	89.6 mm	97.2 mm
12. LENS CONSTRUCTION	10GROUPS	12ELEMENTS	
13. CLEAR APERTURE	FRONT	φ 35.2	
	REAR	φ 8.7	
14. EXIT PUPIL POSITION	W -60.0 mm	T -34.8 mm	
15. MOUNT	CS-MOUNT		
16. FILTER SCREW SIZE	40.5x0.5		
17. DISTORTION	W -3.8%	T -0.1%	
18. WEIGHT	133 g		

#### DC (DIRECT CONTROL)

DRIVE COIL	RESISTOR	200 Ω	(20° C)
	COLOR	RED (+)	BLACK
BRAKE COIL	RESISTOR	700 Ω	(20° C)
	COLOR	YELLOW (+)	GREEN
DRIVE VOLT.	OPEN	LESS THAN +4V	
	CLOSE	OVER THAN 0V	
		W/CLOSING SPRING	



945 East 11<sup>th</sup> Avenue Tampa, FL 33605

Phone: (813) 984-0125

Contact: Sales@pyramidimaging.com

<https://pyramidimaging.com>



機種名  
機種番号

LMVZ540A

1/3" 1.6/5-40mm