



SPECIFICATION

DC AUTO IRIS

1. USE	FOR 1/2" B/W COLOR CAMERA		
2. FOCAL LENGTH	4-10mm		
3. ZOOM RATIO	2.5x		
4. MAX. DIA. RATIO	F1.8		
5. IRIS RANGE	F1.6-360-CLOSE		
6. IMAGE SIZE	φ 8		
7. BACK FOCAL LENGTH	W 8.27	T 13.9	in air
8. FLANGE FOCAL LENGTH	12.5 mm		in air
9. FOCUS RANGE	0.3m		
10. FIELD ANGLE	DIA.	W 122.3 °	T 46.5 °
	HOR.	94.8 °	
	VER.	69.0 °	
11. FIELD OF VIEW AT M. O. D.	W	1163 mm	T 271.0 mm
	HOR.	689.0 mm	
	VER.	434.0 mm	
12. LENS CONSTRUCTION	8 GROUPS 8 ELEMENTS		
13. CLEAR APERTURE	FRONT	φ 24.8	
	REAR	φ 7.6	
14. EXIT PUPIL POSITION	W mm	T mm	
15. MOUNT	CS-MOUNT		
16. FILTER SCREW SIZE	----		
17. DISTORTION	W -18.6%	T -1.6%	
18. WEIGHT	94g		

DC (DIRECT CONTROL)

DRIVE COIL	RESISTOR	190 Ω	(20° C)
	COLOR	RED(+)	BLACK
BRAKE COIL	RESISTOR	1150 Ω	(20° C)
	COLOR	YELLOW(+)	GREEN
DRIVE VOLT.	OPEN	LESS THAN +4V	
	CLOSE	OVER THAN 0V	
		W/CLOSING SPRING	



945 East 11th Avenue Tampa, FL 33605

Phone: (813) 984-0125

Contact: Sales@pyramidimaging.com

<https://pyramidimaging.com>

品名	LMVZ41A
部番	1/2" CS F1.4/4-10mm