



**SPECIFICATION**

**1/3" 1.4/1.6~3.4mm AUTO IRIS**

1. USE	FOR 1/3" B/W COLOR CAMERA		
2. FOCAL LENGTH	1.6~3.4mm		
3. ZOOM RATIO	2.1x		
4. MAX. DIA. RATIO	F1.4		
5. IRIS RANGE	F1.4~360		
6. IMAGE SIZE	φ 6 4.8x3.6		
7. BACK FOCAL LENGTH	W 7.06	T 11.54	in air
8. FLANGE FOCAL LENGTH	12.5 mm in air		
9. FIELD ANGLE	DIA.	W180.0 °	T 106.1 °
	HOR.	180.0 °	84.3 °
	VER.	114.1 °	55.8 °
10. LENS CONSTRUCTION	11GROUPS 12ELEMENTS		
11. CLEAR APERTURE	FRONT	φ 27.8	
	REAR	φ 8.6	
12. EXIT PUPIL POSITION	85.53 mm		
13. MOUNT	CS-MOUNT		
14. FOCUS RANGE	0.2m		
15. FILTER SCREW SIZE	----		
16. WEIGHT	105g		

BS without Amp.

Driving Coil	Resistance	200Ω (20° C)
	Color	Red, Black (Red+Open)
Damping Coil	Resistance	700Ω (20° C)
	Color	Yellow, Green (Yellow+Open)
Driving Voltage	To Open	Less than +4V
	To Close	More than 0V (W/Closing Spring)



**Pyramid Imaging**

945 East 11th Avenue Tampa, FL 33605  
 sales@pyramidimaging.com  
 www.pyramidimaging.com  
 813-786-3785

		1/1	
		1/3" 1.4/1.6~3.4mm DC	
98.11.7		LMVZ164A	