



1/3" 1.4/1.6~3.4mm CS

FOCAL LENGTH	f=1.6~3.4mm	
MAX. DIAMETER (RATIO)	F=1:1.4~16~CLOSE	
PICTURE SIZE	3.6x4.8mm 1/3"	
ANGLE OF VIEW	VER.	114.1 ° ~55.8 °
	HOR.	180 ° ~84.3 °
	DIA.	180 ° ~106.1 °
MINIMUM FOCUS DISTANCE	0.2m	
FLANGE BACK	12.5mm	in air
BACK FOCUS	7.07mm~11.55mm	in air
FILTER SCREW SIZE	—	
FRONT/REAR EFFECTIVE DIA.	φ 27.8mm	φ 8.6mm
MOUNT	CS-MOUNT	
EXIT PUPIL	85.5mm	
TEMPERATURE RANGE	-10~45 C°	
STORAGE TEMPERATURE RANGE	-40~60 C°	
RESOLUTION	100lp/mm (Center)	40lp/mm (Corner)
STOPPER STRENGTH	10kgf/cm	
ENDURANCE TESTS	F:5,000Times	Z:5,000Times I:5,000Times
WEIGHT	98g	



Pyramid Imaging

945 East 11th Avenue Tampa, FL 33605
 sales@pyramidimaging.com
 www.pyramidimaging.com
 813-786-3785

		1/1		
		1/3" 1.4/1.6~3.4mm		
		LMVZ164		
98.11.7				