



1/2" 1.4/ 12mm C		1/3"	
Focal Length		f=12mm±5%	
Max. Diameter (Ratio)		F=1 : 1.4±5%	
Elements		5 Group 6 Elements	
Picture Size		4.8x6.4mm	3.6x4.8
Angle	Ver.	23.0°	17.2°
	Hor.	30.7°	23.0°
	Dia.	38.5°	28.8°
Distortion (TV)		-0.8%	
Shooting Range at M.O.D.	Ver.	123mm	
	Hor.	167mm	
	Dia.	213mm	
Minimum Object Distance		0.3m	
Flange Back		17.526 ^{+0.13} ₋₀ mm in air	
Back Focus		11.12mm in air	
Filter Screw Size		M30.5x0.5	
Front/Rear Effective Dia		F: φ12.3mm	R: φ11.7mm
Mount		C-MOUNT	
Exit Pupil		-38.9mm	
Temperature Range		-10~+45° C	
Storage Temperature Range		-40~+60° C	
Resolution		Center: 100 LP/mm	Corner: 40LP/mm
Stopper Strength		10kgf · cm	
Endurance Tests		Iris: 5,000Times	Focus: 5,000Times
Operating Torque		Iris: 50~600gf · cm	Focus: 100~1000gf · cm
Weight		53g±5g	

LM12NCR