

## Dark Field Lights

Dark field lights are ideal for detecting edges and contours.

The standard light beam angle is 10°.

The dark field lights have a diffuser for better evenness of illumination.

Bracket LAD3 4011 is included (for details see "Lighting head brackets").



945 East 11th Avenue Tampa, FL 33605


Phone: (813) 984-0125

Contact: Sales@ pyramidimaging.com

https://pyramidimaging.com



## **Mechanical Dimensions**



Step files available on request

<b>Color Information</b>		
Replace "X" in order number by one character <sup>1</sup>	Color	Wavelength (nm)
Н	Red	617
W	White	
R	IR	880
В	Blue	465
G	Green	520
U	UV	395

<sup>&</sup>lt;sup>1</sup> Example for red dark field light: SAH3 4H072

Order Information								
Order number	Sizes (mm)		Light	Controller <sup>2</sup>				
	outer ø	inner ø	height	beam angle	continuous/ switching mode	strobe mode		
PAD3 4025 <sup>3,5</sup>	25	15	9.5	5°	1 A	8 A		
SAX3 4072	72	42	13.5	10°	1 A	8 A		
SAX3 4103	103	73	13.5	10°	1 A	8 A		
SAX3 4166	166	136	13.5	10°	1 A	8 A		
SAX3 4213	213	183	13.5	10°	1 A 3 A <sup>4</sup>	8 A 24 A <sup>4</sup>		
SAX3 4276	276	246	13.5	10°	1 A 3 A <sup>4</sup>	8 A 24 A <sup>4</sup>		

- <sup>2</sup> See "Controller selection" for details
- Available only in red light color
  For light colors white, blue, green and UV
  Screw-in depth (M1,6) max. 2 mm

## **Options**

- Cable length and type see "Order options"
- Custom light beam angle see "Order options"