



		1.1"	2.5/6.5mm C	1.1"	1"	2/3"
FOCAL LENGTH		f=6.5mm				
F-NUMBER		F=2.5-16				
PICTURE SIZE		10.6x14.1mm		9.6x12.8mm		6.6x8.8mm
ANGLE OF VIEW (∞)	VER. ANGLE	78.7°		73.0°		53.5°
	HOR. ANGLE	95.7°		89.9°		68.1°
	DIA. ANGLE	109.1°		103.4°		80.8°
DISTORTION (TV)		-1.51%		-1.27%		-0.68%
FIELD OF VIEW (MINIMUM FOCUS DISTANCE)	VER.	190mm		172mm		117mm
	HOR.	256mm		231mm		157mm
	DIA.	323mm		292mm		197mm
MINIMUM FOCUS DISTANCE		0.1m				
FLANGE BACK		17.526mm in air				
BACK FOCUS		10.9mm in air				
FILTER SCREW SIZE		M82x0.75				
FRONT/REAR EFFECTIVE DIA.		FRONT φ46.0mm		REAR φ18.5mm		
MOUNT		C-MOUNT				
EXIT PUPIL		-61.7mm				
TEMPERATURE RANGE		-10~+50°C				
STORAGE TEMPERATURE RANGE		-20~+60°C				
RESOLUTION CENTER/CORNER		CENTER 200lp/mm		CORNER 100lp/mm		
WEIGHT		300g				

NOTE: Specifications and availability are subject to change without notice

注) 本仕様については、予告なしに変更する場合があります。



		尺度	1/1	工場番号
		機種名	1.1" F2.5 f=6.5mm	
2018.11.15	フィルター枠形状変更	機種番	LM6FC24M 外観図	
2018.04.05	作成年月日			