



2X REAR ADAPTER FOR RESOLV4K

FOCAL LENGTH: 320.0mm
 SENSOR COVERAGE: 32mm (APS FORMAT)
 DISTORTION: 0.17%
 INPUT ANGLE: 2.863°
 MAX PUPIL Ø: 16.5mm (19.0mm RESOLV4K FIXED CONFIG)
 IMG NA: 0.0258
 WAVELENGTH: 430 - 670nm VIS
 430 - 1000nm VNIR
 900 - 1700nm SWIR
 TRANSMISSION: 95.2% (445-655nm VIS)



945 East 11th Avenue Tampa, FL 33605
 Phone: (813) 984-0125
 Contact: Sales@pyramidimaging.com
<https://pyramidimaging.com>

OUTLINE

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES		PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NAVITAR. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NAVITAR IS PROHIBITED.			
SCALE:	1.5:1			2X, (32mm APS) REAR ADAPTER	
WEIGHT:	1.04 lbmass	DO NOT SCALE DRAWING		SIZE	PART NUMBER
DR BY:	J. WILLIAMSON			B	1-81104
CH BY:	PB			REV	A
PROJECT #:	E3527				
DATE DR:	7/12/2017				