
SCALE 1:1



WORKING DISTANCE = 90mm FINE FOCUS TRAVEL = 10mm (OL SHOWN IN EXTENDED POSITION)

ENCODED MOTOR AND HALL EFFECT CABLE INFORMATION:

- FOCUS / HE CABLE LENGTH = 0.15m - USE NAVITAR #1-40284 (1.8m), 1-40285 (1.2m), 1-40286 (0.6m) TO CONNECT TO NAVITAR ENCODER CONTROLLERS (1-40237,1-40238, 1-40242)

FF MOTOR 6 POSITION FEMALE CONNECTOR (MOLEX #50-57-9406) HE SENSOR 4 POSITION FEMALE CONNECTOR (MOLEX #50-57-9404)

ENCODED FF MOTOR PINOUT

PIN 1 = +5Vdc (ORANGE)

PIN 2 = MOTOR CHAN A (WHITE)

PIN 3 = MOTOR CHAN B (BLACK)

PIN 4 = MOTOR GROUND (YELLOW)

PIN 5 = MOTOR + (RED)

PIN 6 = MOTOR - (BROWN)

PIN HE SENSOR PINOUT
PIN 1 = COMMON
PIN 2 = FAR LIMIT
PIN 3 = +5vDC
PIN 4 = NEAR LIMIT



OUTLINE

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES [MM] AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NAVITAR. ANY REPRODUCTION IN PART		NINTAR	
SCALE: 2:1	OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NAVITAR IS PROHIBITED.		ROCHESTER, NEW YORK	
WEIGHT: 0.89 lbmass	0.0 inch 1.0		MTD FF FNO 4 OV LENC	
DR BY: J. WILLIAMSON			MTR FF, ENC, 1.0X LENS ATTACHMENT	
CH BY: PB	0.0 mm 25.0		, (1 1) (OI IIVIEI (1	
PROJECT #: E3576	DO NOT SCALE DRAWING	SIZE	PART NUMBER	REV
DATE DR: 11/17/2017	$\oplus \Box$	С	1-81204M3	Α