



2/3" 1.4/12mm C		1/2"	1/3"
FOCAL LENGTH	f=12mm		
MAX. DIAMETER (RATIO)	F=1:1.4,4,8,16		
PICTURE SIZE	6.6x8.8mm	4.8x6.4	3.6x4.8
ANGLE	VER. ANGLE	26.2°	21.4°
	HOR. ANGLE	38.3°	28.3°
	DIA. ANGLE	46.8°	35.0°
DISTORTION (TV)	-0.07%	-0.05%	-0.04%
	500mm	0.025x	
WORKING DISTANCE	400mm	0.031x	
	300mm	0.041x	
OPTICAL MAGNIFICATION	200mm	0.061x	
	150mm	0.080x	
MINIMUM FOCUS DISTANCE	0.15m		
FLANGE BACK	17.526 mm in air		
BACK FOCUS	11.7mm in air		
FILTER SCREW SIZE	M27x0.5		
FRONT/REAR EFFECTIVE DIA.	前φ15.8mm	後φ14.1mm	
MOUNT	C-MOUNT		
EXIT PUPIL	-215mm		
TEMPERATURE RANGE	-10~+45°C		
STORAGE TEMPERATURE RANGE	-40~+60°C		
RESOLUTION CENTER/CORNER	中心100本/mm	周辺80本/mm	
WEIGHT	g		

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。

		尺度	1/1	承認	入木	製図	入木
		機種名	2/3" F1.4 f=12mm				
			1-25552				
2014.2.25		作成年月日					