

OUTLINE

POWER INPUT

AC power supply via universal power cord.

USB INTERFACE

Connection to PC made via USB cable.

ROTARY ENCODER

Manual controller yields .1% resolution per turn

LIGHTING CABLE INPUT

Compatible with barrel power cables with connector type: 2.1mm ID, 5.5mm OD plug cable.



Pyramid Imaging

Tampa, FL
sales@pyramidimaging.com
www.pyramidimaging.com
 813-786-3785

UNLESS OTHERWISE SPECIFIED
 DIMENSIONS ARE IN INCHES [MM]
 AND INCLUDE CHEMICALLY
 APPLIED OR PLATED FINISHES

SCALE: 1:1

WEIGHT: 0.45 kg

DR BY: J. WILLIAMSON

CH BY: PB

PROJECT #: E3673

DATE DR: 9/23/2020


PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS
 DRAWING IS THE SOLE PROPERTY OF
 NAVITAR. ANY REPRODUCTION IN PART
 OR AS A WHOLE WITHOUT THE WRITTEN
 PERMISSION OF NAVITAR IS PROHIBITED.

0.0 inch 1.0

0.0 mm 25.0

DO NOT SCALE DRAWING



CONTROLLER, DESKTOP, DIGITAL
 READOUT

SIZE	PART NUMBER	REV
B	SK-1-81400	1