Pyramid Imaging Ruggedized Washdown Area Front Light Model#: MT-FL300x150





The MT-FL300x150 is a cost effective and "integrator ready" high power illuminator with versions that include a built-in constant current driver version (simply provide 24VDC to operate), Strobe-only version (simply provide 24VDC and trigger signal) and ULC-2 version (external constant current controller version for DC & strobe operation).

- HIGH POWER, LARGE AREA FLOOD LIGHT
- IP67 RATED WATER TIGHT ENCLOSURE
- AVAILABLE IN VARIOUS WAVELENGTHS(COLOR)
- RUGGED BLACK ANODIZED HOUSING
- OPTIONAL 0-10VDC INTENSITY CONTROL

SP	EC	IEI	C	ΔΤΙ	NS
JF.				-11	C V I

Current Consumption	3.3A @ 24VDC
Finish	Black Anodized Aluminum
Wavelength	White (6000K), Red, Green, Blue, IR, UVS, UVL
Weight	15lbs / 6,803g
Operating Temperature	-30°C - +60°C
Illuminance	168,000 Lux / 7,200 Lumens
Compliance	CE/RoHS
Seal	Gasket
Lifetime Hours	75,000 Hours

Active Area	Enclosure Dimensions		
L: 11.82in/ 300.23mm	L: 15.5in / 393.7mm		
W: 5.91in/150.11mm	W: 7.75in / 196.85mm		
	H: 4.26in / 108.1mm		

IEC 62471 COMPLIANT		
LED COLOR	RISK GROUP	
RED, IR	Exempt	
UVS Green, RGB, White, Blue	1	
UVS (365NM)	2	

DOMINANT WAVELENGTH:		
PARTS	COLOR	
MT-FL300x150-W	White 6000K	
MT-FL300x150-R	Red 630nm	
MT-FL300x150-B	Blue 470nm	
MT-FL300x150-G	Green 530nm	
MT-FL300x150-IR	Infrared 850nm	
MT-FL300x150-UVL	UVL 395nm	
MT-FL300x150-UVS	UVS 365nm	


## **APPLICATIONS**

Large Work Envelopes	Washdown Applications
<ul> <li>Packaging Food &amp; Drugs</li> </ul>	• Liquid Filling
• Wet Locations	



## Wiring Diagram

## **Power Connector On light**



Note: Requires cable such as Turck part# RKM30-\*XM, not included (\*X=Length in Meters)

Pin#	Cable Color		FUNCTION		
		Non-dimming Version	<b>Optional Dimming Version</b>		
1	Green/Yellow	n/a	0-10V DC (dimming)		
2	Brown	24V DC	24V DC		
3	Blue	0V DC	0V DC		

## Contact Us:

Specifications are subject to change Copyright ©Metaphase Technologies. MP140004

