

## MB-FL

MetaBright™ Front Lights feature high density LED array placement and proprietary *Metaphase* thermal management technology to assure maximum LED lifetime and lowest cost of ownership. Our Front Lights are designed for longer working distances and feature rugged housings such as those found in industrial robotics work envelopes.

Familiar four-hole mounting pattern makes it easy to replace older style robotic LED lights without having to rework your existing tooling or end-effectors. Patented optics and thermal control system assures a lifetime of cost effective illumination. Lightweight one-piece machined aluminum housing and Stainless-Steel waterproof versions are now available.



### FEATURES

- Homogenous light output that provides high intensity illumination
- Shock and vibration resistant
- LED thermal management for stable performance
- Industry proven for virtually any lighting application
- Flicker free performance and instant start up with Metaphase analog driver technology
- Economical, low cost
- An ideal light for many applications
- Built-in Constant Current Driver with 0-10VDC intensity control, compatible with DDC-3 and ILD-35 Dimmers

### WAVELENGTHS

Order ID	Description / nanometers
<b>W</b>	White (6000K), Nominal
<b>R</b>	Red / 630nm
<b>G</b>	Green / 530nm
<b>B</b>	Blue / 470nm
<b>IR850</b>	Infrared / 850nm
<b>UV365</b>	Ultraviolet Short / 365nm
<b>UV395</b>	Ultraviolet Long / 395nm

### GENERAL SPECIFICATIONS

<b>Power Source:</b>	24VDC ±5%
<b>Cable (Standard):</b>	10-foot cable with flying leads
<b>Housing:</b>	Black Anodized Aluminum
<b>Ambient Temp:</b>	-20°C to 40°C
<b>Lifetime Expectancy:</b>	75,000 hours (except UV)

Front Lights

MB-FL

Front Lights							
MODEL	Dimensions W x L x H Inches (cm)	Active Area Inches (cm)	Weight lbs (grams)	Cable QTY	Cable Length	Cable AWG/ Conductors	Max Input Current @24VDC
<b>Heritage Designs</b>							
FL201	1.70 x 3.40 x 1.0 (4.32 x 8.64 x 2.54)	1.45 x 2.90 (3.68 x 7.37)	.30 (136)	1	10ft	24/4	.21A
FL301	3.4 x 4.1 x 1.0 (8.64 x 10.3 x 2.54)	1.64 x 3.11 (4.17 x 7.89)	.50 (227)				.26A
FL401	3.4 x 6.6 x 1.0 (8.64 x 16.8 x 2.54)	3.06 x 5.50 (7.77 x 14.0)	1.10 (500)				1.2A
FL411 (IP65)	3.99 x 7.89 x 1.0 (10.14 x 20.0 x 2.54)	2.90 x 5.40 (7.36 x 13.71)	1.50 (680)			18/4	1.2A

Wiring (4 conductor with Intensity Control)**	
Wire Color	Function
RED	+24VDC
WHITE	0-10VDC INTENSITY CONTROL
BLACK	GROUND (24V RTN)
GREEN	SIGNAL GROUND

Wiring (4 conductor without Intensity Control)	
Wire Color	Function
RED	+24VDC
WHITE	+24VDC
BLACK	GROUND (24V RTN)
GREEN	GROUND (24V RTN)

M12 (5 position male)**	
Pin #	Function
1	+24VDC
2	0-10VDC Intensity Control
3	GROUND (24V RTN)
4	SIGNAL GROUND
5	No Connection

The M12 connector option is not recommended for lights rated more than 4 amps

Wiring with ULC-2	
Wire Color	Function
RED, WHITE (+)	LED INPUT
BLACK, GREEN (-)	

Terminated within a 2 position ULC-2 output connector (Phoenix Contact P/N: BCP-508-2)

\*\*Note: The 0-10VDC Intensity Control input can accept voltages from 0-24VDC where the light will operate at full intensity in the 10-24VDC range. The light is proportionally dimmer for any Intensity Control voltage less than 10VDC and the light is OFF at approximately 0V or not connected (floating).

**MB-FL**

PART NUMBER KEY													
MODEL	SIZE	-	WAVELENGTH	-	DRIVER* (most common)	-	LENS	-	DIFFUSER	-	CABLE LENGTH	-	CONN.** (most Common)
MB-FL	XXX	-	XXXXX	-	XXXXX	-	XXX	-	XX	-	XXX	-	XXXX
<b>MB-FL</b>	<b>201</b> (1.3x2.5") <b>301</b> (2.5x2.5") <b>401</b> (3.0x5.0") <b>411</b> (3.0x5.0")		<b>W</b> (White 6000K, Nominal) <b>R</b> (Red 630nm) <b>G</b> (Green 530nm) <b>B</b> (Blue 470nm) <b>IR850</b> (Infrared 850nm) <b>UV365</b> (UV Short 365nm) <b>UV395</b> (UV Long 395nm)		<b>24Z</b> <b>24Z-TRG</b> <b>24-ILD</b> <b>24-ILSXXX</b> <b>24-BISXXX</b> <b>U<sup>1</sup></b>		<b>L11</b> (11°) <b>L30</b> (30°) <b>L34</b> (34°)		<b>CC</b> (Clear Cover) <b>D2</b> (Single Matte) <b>D3</b> (TIR/SLK) <b>D4</b> (Milky White) <b>D5</b> (Double Matte)		<b>5M</b> <b>10M</b>		<b>M12D<sup>1 2</sup></b> <b>BC<sup>1 3</sup></b>
Example 1: <b>MB-FL301-G-24Z-L30-D2</b>					Example 2: <b>MB-FL411-W-24-TRG-L11-CC-M12D</b>					<sup>1</sup> Not available in lights exceeding 4A input current <sup>2</sup> Default cable length for an M12D connector is 19 inches <sup>3</sup> Default cable length for a Barrel Connector is 10 feet			

Contact Metaphase Technologies or your local representative for options such as custom diffusers, lenses, polarizers, IP-rated enclosures for harsh environments, higher intensity, custom wavelengths, higher uniformity, etc. Not all options are available for all lights.

\*(Link to Driver Options Key)

\*\* (Link to Connector Key)

**MB-FL**

Sample Model Number: **MB-FL301-G-24Z-L30-D2**

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	8/8/2013	
B	CHANGED COVER SCREW HOLE PATTERN- SEE SHEET 2	8/12/2013	
C	CHANGED DIFFUSER TO STANDARD PART	2/12/2018	

SEE SHEET 2 FOR EXPLODED VIEW AND BOM.

Metaphase Technologies, Inc. 211 Sinclair Road, Suite 100, Bristol, PA. 19007 215-639-8699 Fax 215-639-0977										
QUANTITY: 1 per assy.	TOLERANCE/FINISH UNLESS OTHERWISE SPECIFIED	THIS DOCUMENT IS THE PROPERTY OF METAPHASE TECHNOLOGIES, INC. WHOM MAY LOAN IT, SUBJECT TO RETURN UPON DEMAND. IT INCLUDES CONFIDENTIAL & PROPRIETARY INFORMATION WHICH MAY NOT BE DISCLOSED TO ANY THIRD PARTY, AND/OR USED FOR ANY PURPOSE CONTRARY TO ITS INTENDED USE, WITHOUT THE EXPRESSED PRIOR WRITTEN CONSENT OF METAPHASE TECHNOLOGIES, INC.								
MATERIAL: Per BOM	INCHES [MM] 125V RMS [240-250V]									
FINISH: Black Anodize	X .XX XXX [1.76] [2.29] .010 [1.13] ±.005 ANGLES ±1°									
TREATMENT: N/A										
Approval Signature _____	Date // /	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2">TITLE: Top Assembly, 3" Front Light</td> </tr> <tr> <td>USED ON: Per customer</td> <td>REV: C</td> </tr> <tr> <td>SIZE: B</td> <td>DRAWING NUMBER: FL301-1</td> </tr> <tr> <td>SCALE: 12</td> <td>SHEET 1 OF 1</td> </tr> </table>	TITLE: Top Assembly, 3" Front Light		USED ON: Per customer	REV: C	SIZE: B	DRAWING NUMBER: FL301-1	SCALE: 12	SHEET 1 OF 1
TITLE: Top Assembly, 3" Front Light										
USED ON: Per customer	REV: C									
SIZE: B	DRAWING NUMBER: FL301-1									
SCALE: 12	SHEET 1 OF 1									

**COMPLIANCE**



**CONTACT US**



Tampa, FL  
Phone: (813) 984-0125  
Contact: Sales@pyramidimaging.com  
<https://pyramidimaging.com>