

型番	Product Name	HF50XA-5M
焦点距離 [mm]	Focal length [mm] (design value)	50 (48.49)
絞り範囲 (F値)	Iris range (Fnumber)	F2.4-F16
画角 (H × V)	Angle of view	10.4° × 7.8° (2/3")
フォーカス範囲 (レンズメカ先端より) [mm]	Working distance (from front of lens barrel) [mm]	∞ - 200
操作方法:フォーカス	Operation of focus	Manual
操作方法:アイリス	Operation of iris	Manual
フィルタ径 [mm]	Filter thread [mm]	M30.5 × 0.5
マウント	Mount	C-mount
質量 (約) [g]	Weight (approx.) [g]	95
適合センサーサイズ (標準)	Sensor size (std.)	2/3" (3.45μm)
適合センサーサイズ (最大)	Sensor size (max.)	1.1" (4.5μm)
バックフォーカス (空気換算長) [mm]	Back focal length (in air) [mm]	24.48
フランジバック [mm]	Flange back [mm]	17.526
入射瞳位置 (マウント面から) [mm]	Entrance pupil position (from Mount) [mm]	-19.79
射出瞳位置 (結像面より) [mm]	Exit pupil position (from image plane) [mm]	-64.87
前側主点 (マウント面から) [mm]	Front principal point (from Mount) [mm]	-7.88
後側主点 (マウント面から) [mm]	Rear principal point (from Mount) [mm]	-30.97
主点間隔 [mm]	Distance between the principal points [mm]	-23.08
TV歪み [%]	TV distortion [%]	0.01
外形寸法 [mm]	Dimension [mm]	φ33.0 × 66.5
主光線入射角度 [°]	Chief Ray Angle [°]	4.79
周辺光量比 (F4.0・対角端) [%]	Relative illumination [%] (Aperture: F4.0, Image height : at diagonal)	97
周辺光量比 (開放・対角端) [%]	Relative illumination [%] (Aperture: at full open, Image height : at diagonal)	65
使用温度範囲	Operation Temperature Range	-10°C ~ +50°C
保存温度範囲	Storage Temperature Range	-30°C ~ +60°C


These specifications are subject to change without notice.

Entrance pupil position and Exit pupil position are calculated by "chief ray of 60% image height".

17-Oct-22



HF50XA-5M



レンズ本体：外観図
Outline drawing
HF50XA-5M

SS00002586-00

Aug 15, 2017