


MetaLight™ Linear Front Light Model#: LFL201



- Shock and Vibration proof up to 10 G's per MIL-STD-910F the highest industry standards
- Solid one-piece machined aluminum housings and thermal potting
- Performance extends to rugged environments
- Can be configured for wavelength and other specifications
- Equipt with pairing and axial rotation capabilities

Part #	Color	Power Supply	Specifications:	
LFL201-W-24	White 5500K	24 volt power supply available upon request.	Current Consumption	0.15A
LFL201-R-24	Red 630nm		Housing	Aluminum
LFL201-B-24	Blue 455nm		Finish	Anodized
LFL201-G-24	Green 530nm		Intensity Uniformity	+/-5%
LFL201-IRN-24	Infrared 850nm		Operating Temperature	120° F Max
LFL201-IRL-24	Infrared 880nm		Illuminance	75,000 Lux
LFL201-UVL-24	UV 395nm		Compliance	CE/RoHS
LFL201-UVS-24	UV 365nm		Lifetime Hours	75,000 Hours

10 ft. flying leads come standard on all products.
Light features built-in constant current driver.
No expensive controller required.

Active Area	Dimensions
1 in x 5.6 in 25.4mm x 143mm	6in x 1.25in x 1.89in 153mm x 31.75mm x 47mm

ORDERING INFORMATION:

• L F L 2 0 1 - - 2 4 -

W White 5500k
R Red 630nm
G Green 530nm
B Blue 455 nm
IRL Infrared 880nm
UVL (long) 395nm
UVS (short) 365nm

***BLANK**
T 10 ft. Flying Leads
ILD M12 Quick Disconnect
ILS In Line Dimmer
 In Line Strobe (customer provide trigger info)

