


2-PHASE MOTOR PINOUT

- PIN 3 = +5Vdc
- PIN13 = COMMON
- PIN 8 = FAR LIMIT
- PIN 12 = NEAR LIMIT
- PIN 1 = MOTOR A+
- PIN 7 = MOTOR A-
- PIN 6 = MOTOR B+
- PIN 11 = MOTOR B-



15 PIN HIGH DENSITY
D-SUB

Pyramid Imaging
 4951 Adamo Dr. Suite 224
 Tampa, FL 33605-5919
 Phone: 813.984.0125 Fax: 866.874.9521
www.pyramidimaging.com

USED ON:

MATERIAL:

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

TOLERANCES:
 DEC. .XXX ± .005
 DEC. .XX ± .010
 FRACT. ± 1/64
 ANGLES ± 30'
 CONCENTRICITY .003 TIR
 BREAK ALL SHARP EDGES .005 MIN. .010 MAX
 MAX. SURF. ROUGHNESS 32 √


FINISH:

CHAMFER ALL THREADS 30° TO ROOT DIAM.

P/N SUFFIX DEFINITION
 -1 CONVERSION COATING
 -2 PAINTING
 -3 MARKING
 -R REWORK

SCALE: 1:1
DR.: R. PODLENA
CH.: P. BONAFEDE
APP.:
DATE DR.: 8/18/2003
DO NOT SCALE DRAWING

THE CONTENTS OF THIS DOCUMENT ARE PROPRIETARY TO NAVITAR, ITS USE IS AUTHORIZED ONLY FOR RESPONDING TO REQUEST FOR QUOTATION OR PERFORMANCE OF WORK FOR NAVITAR



OUTLINE



MOTORIZED (STEPPER) 6x w/2 POS LS (HE)

SIZE	1-62605	REV
B	SHEET 1 OF 1	A