


2-PHASE MOTOR PINOUT

PIN 3 = +5Vdc
 PIN13 = COMMON
 PIN 8 = FAR LIMIT
 PIN 12 = NEAR LIMIT
 PIN 1 = MOTOR A+
 PIN 7 = MOTOR A-
 PIN 6 = MOTOR B+
 PIN 11 = MOTOR B-



15 PIN HIGH DENSITY
D-SUB



Pyramid Imaging




945 East 11th Avenue Tampa, FL 33605

sales@pyramidimaging.com

www.pyramidimaging.com

813-786-3785

OUTLINE

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES		THE CONTENTS OF THIS DOCUMENT ARE PROPRIETARY TO NAVITAR, ITS USE IS AUTHORIZED ONLY FOR RESPONDING TO REQUEST FOR QUOTATION OR PERFORMANCE OF WORK FOR NAVITAR		<div>NAVITAR</div> <div>ROCHESTER, NEW YORK</div>		
SCALE: 1:1		<div><div>0.0inch1.0</div><div></div><div>0.0mm25.0</div></div> <div>DO NOT SCALE DRAWING</div> <div></div>		MTR (STEP) 6X w/LS (HE) & ROT. CP		
WEIGHT: 1.6lbm				SIZE B	1-62608 SHEET 2 OF 2	REV B
DR: R. PODLENA						
CH: P. BONAFEDE						
PROJECT #:						
DATE DR: 8/18/2003						