

6' LONG CABLE w/ 3.5mm MONO JAX
 0-4Vdc 1.2 AMP MAX
 LUMINOUS INTENSITY
 3200 mcd
 REQUIRES FRESNEL LENS ATTACHMENT



945 East 11th Avenue Tampa, FL 33605
 Phone: (813) 984-0125
 Contact: Sales@pyramidimaging.com
<https://pyramidimaging.com>

OUTLINE

USED ON:

MATERIAL:

FINISH:

CHAMFER ALL THREADS 30° TO ROOT DIAMETER



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

TOLERANCES AS FOLLOWS
 DEC. .XXX ± .005
 DEC. .XX ± .010
 FRACT. ± 1/64
 ANGLES ± 30°
 CONCENTRICITY .003 TIR
 BREAK ALL SHARP EDGES .005 MIN. .010 MAX.
 MAX. SURF. ROUGHNESS: $\sqrt{32}$

SCALE: 1:1
 DR: DJM
 CH: PB
 APP: PB
 DATE DR: 11/15/2002
 DO NOT SCALE DRAWING

P/N SUFFIX DEFINITION

- 1 CONVERSION COATING
- 2 PAINTING
- 3 MARKING
- R REWORK



NAVITAR
 ROCHESTER, NEW YORK

WHITE 60 LED RING LIGHT

SIZE	1-62350_OL	REV
A	SHEET 1 OF 1	A