



Pyramid Imaging
 945 East 11th Avenue
 Tampa FL 33605
sales@pyramidimaging.com
www.pyramidimaging.com
 813-984-0125

OUTLINE

USED ON:

MATERIAL:

UNLESS OTHERWISE SPECIFIED
 DIMENSIONS ARE IN INCHES AND
 INCLUDE CHEMICALLY APPLIED
 OR PLATED FINISHES

FINISH:

CHAMFER ALL THREADS 30°
 TO ROOT DIAMETER

TOLERANCES AS FOLLOWS
 DEC. .XXX ± .005
 DEC. .XX ± .010
 FRACT. ± 1/64
 ANGLES ± 30'
 CONCENTRICITY .003 TIR
 BREAK ALL SHARP EDGES
 .005 MIN. .010 MAX.
 MAX. SURF. ROUGHNESS: $\sqrt{32}$

P/N SUFFIX DEFINITION
 -1 CONVERSION COATING
 -2 PAINTING
 -3 MARKING
 -R REWORK

SCALE: 1:1

DR: R. PODLENA
 CH: P. BONAFEDE
 APP:
 DATE DR: 3/31/2003
 DO NOT SCALE DRAWING

THE CONTENTS OF THIS
 DOCUMENT ARE PROPRIETARY
 TO NAVITAR, ITS USE IS
 AUTHORIZED ONLY FOR
 RESPONDING TO REQUEST FOR
 QUOTATION OR PERFORMANCE
 OF WORK FOR NAVITAR

0.0 inch 1.0
 0.0 mm 25.0

| | |
|--|-----------------------------------|
|  ROCHESTER, NEW YORK | |
| PARALLEL COAX. 8mm INPUT | |
| SIZE A | 2-60263_OL SHEET 1 OF 1 |
| REV E | |