

5 PIN CONNECTOR (MOTOR)

- PIN 1 = MOTOR 1
- PIN 2 = MOTOR 2
- PIN 3 = MOTOR 3
- PIN 4 = MOTOR 4
- PIN 5 = MOTOR 5

5 POS MOLEX CONNECTOR
(MOLEX #70107-0004)

4 POS MOLEX CONNECTOR
(MOLEX #70107-0003)

4 PIN CONNECTOR (SENSOR)

- PIN 1 = COMMON
- PIN 2 = FAR LIIMIT
- PIN 3 = +5Vdc
- PIN 4 = NEAR LIMIT

72.0 ±1.0
[1.83 Meters]

15 PIN HD MALE
D-SUB CONNECTOR

CONNECTOR PINOUT

- PIN1 = PIN2
- PIN 3 = +5Vdc
- PIN 4 = MOTOR 4
- PIN 5 = MOTOR 2
- PIN 8 = FAR LIMIT
- PIN 10 = MOTOR 3
- PIN 12 = NEAR LIMIT
- PIN 13 = COMMON
- PIN 14 = MOTOR 5
- PIN 15 = MOTOR 1

15 PIN HD FEMALE D-SUB

OUTLINE



945 East 11th Avenue Tampa, FL 33605

Phone: (813) 984-0125

Contact: Sales@ pyramidimaging.com

<https://pyramidimaging.com>

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES		PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NAVITAR. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NAVITAR IS PROHIBITED.	
SCALE:	1:1		
WEIGHT:	N/A		
DR BY:	CLB		
CH BY:	PB		
PROJECT #:	E3036		
DATE DR:	4/5/2013	CABLE HARNESS, 5 PHASE	
DO NOT SCALE DRAWING	SIZE B	1-40170 SHEET 3 OF 3	REV A

