



features

- Camera Link® PCI Express x4 interface board
- Camera Link® cable MDR/MDR 3,0 m (2 pieces)
- power supply/flash cable Hirose 5,0 m
- international power supply 12V/2,0A, incl. adapter cable with Hirose/6-pin connector for HXC13
- software for Windows®
- camera not included

interface card

article number	11014581
name	PCIe-CL microEnable IV AD4-CL
features	<ul style="list-style-type: none"> ▪ Base, Dual Base, Medium and Full configurations support ▪ quad lane PCI Express interface ▪ 2 x MDR26 interface ▪ 256 MB image buffer

cable

article number	11008811
name	2x cable Camera Link MDR/MDR 3,0 m
features	<ul style="list-style-type: none"> ▪ Camera Link® interface cable with MDR connectors ▪ length 3,0 m

process interface cable

article number	11008801
name	cable Hirose 6 wires, 5,0 m
features	<ul style="list-style-type: none"> ▪ Hirose process interface cable for HXC13 cameras ▪ 6-pin ▪ with open wires ▪ length 5,0 m

power supply

article number	11046251
name	power supply Hirose
features	<ul style="list-style-type: none"> ▪ international power supply 12V/2.0A, incl. adapter cable with Hirose/6-pin connector for HXC13 ▪ length 5,0 m ▪ adapter for EU, US, UK, AU and KR

software

Baumer GAPI	for Windows®
-------------	--------------