

High Flex Right Angle Certified Camera Link - CLCP*-xx-P

Product Outline

Intercon 1's high performance right angle Camera Link cable increases versatility and resilience in restricted space applications.

The unique right angle overmolding available in up, down, left and right orientations allows for immediate turns behind the interface that are specific to your application needs eliminating the need for minimum bend radius concerns.

The high flex cable construction adheres to the Camera Link specifications and performs with a projected flex life of over 1 million flex cycles. Independent testing of the assembly has surpassed 5 million flex cycles.



Main Product Specifications

Features

- Robust high flex cable
- 360 degree shielding
- Durable overmolding
- Right angle interface in up, down, left, and right configurations
- RoHS Compliant



Cable Specifications

Overall Diameter	.375 Inches
Max Temperature	80 Degrees C
Jacket Color	Black
UL/CSA Rated	Yes
Min. Bend Radius	3.75 Inches
Flame Rating	FT-1

Primary Components

Cable	11 Individually Shielded Twisted Pairs
Connector A	26 Pos MDR
Connector B	26 Pos MDR

Ordering Information

Order Number	Description
CLCP*-xx-P	High Flex Camera Link

Replace xx with length in meters

Replace * with "U" for up, "D" for down, "R" for right or "L" for left

For cables longer than 10 meters contact customer service

Custom variations available. Please contact customer service for additional information.

Pyramid Imaging

www.PyramidImaging.com • Sales@PyramidImaging.com

Phone: 813-984-0125 • Fax: 866-874-9521