

## Mini Camera Link - MCLCP-xx-MP

### Product Outline

Mini Camera Link offers a smaller interface without sacrificing performance and quality.

This high performance cable is capable of withstanding extreme outside stress such as flexing, high temperatures, outdoor elements, and electrical noise without exhibiting electrical degradation.

The rugged overmold offers additional benefits for added strain relief and durability under motion, installations, and vibration. The thumbscrews ensure proper mating and constant connectivity.



### Main Product Specifications

#### Features

- 1 million + flex life design
- Overmolded connectors
- Robust jacket capable of outdoor use
- 360 degree shielding
- RoHS Compliant
- Right angle configurations available



#### Cable Specifications

Cable Specifications	
Overall Diameter	.270 Inches
Max Temperature	80 Degrees C
Jacket Color	Black
UL/CSA Rated	Yes
Min. Bend Radius	2.70 Inches
Flame Rating	vw-1 / FT-1

#### Primary Components

Primary Components	
Cable	11 Individually Shielded Twisted Pairs
Connector A	26 Pos SDR (HDR)
Connector B	26 Pos SDR (HDR)

### Ordering Information

Order Number	Length		Description
	Meters	Feet	
MCLCP-1.0-MP	1.0	3.28	Mini CL to Mini CL High Flex
MCLCP-2.0-MP	2.0	6.56	Mini CL to Mini CL High Flex
MCLCP-3.0-MP	3.0	9.84	Mini CL to Mini CL High Flex
MCLCP-4.0-MP	4.0	14.76	Mini CL to Mini CL High Flex
MCLCP-5.0-MP	5.0	16.4	Mini CL to Mini CL High Flex

Custom variations are available. Please contact customer service for additional information.