

Mini Camera Link to Standard Camera Link - MCLCP-xx-P

Product Outline

Mini Camera Link offers a smaller interface without sacrificing performance and quality.

Both standard and mini CL interface with the same pin configuration allowing cables to convert between both CL styles. This enables the use of a CL system that fits your specific needs.

Mini CL features an overmolded connector for the best strain relief. The high flex cable and locking thumbscrews add additional benefits when used in a motion application.

Durability is ensured with a unique jacket consisting of a blend of Teflon and Dacron creating a tough material that is both flexible and robust.



Main Product Specifications

Features

- 1 million + flex life design
- Overmolded connectors
- Robust jacket capable of outdoor use
- 360 degree shielding
- RoHS Compliant



Cable Specifications	
Overall Diameter	.270 Inches
Max Temperature	80 Degrees C
Jacket Color	Black
UL/CSA Rated	Yes
Min. Bend Radius	2.70 Inches
Flame Rating	vw-1 / FT-1

Primary Components	
Cable	11 Individually Shielded Twisted Pairs
Connector A	26 Pos SDR (HDR)
Connector B	26 Pos MDR

Ordering Information

Order Number	Length		Description
	Meters	Feet	
MCLCP-1.0-P	1.0	3.28	Mini CL to Standard CL High Flex
MCLCP-2.0-P	2.0	6.56	Mini CL to Standard CL High Flex
MCLCP-3.0-P	3.0	9.84	Mini CL to Standard CL High Flex
MCLCP-4.0-P	4.0	14.76	Mini CL to Standard CL High Flex
MCLCP-5.0-P	5.0	16.4	Mini CL to Standard CL High Flex

Custom variations are available. Please contact customer service for additional information.

