

High Flex Power Over Mini Camera Link - POMCLP-xx-MP

Product Outline

This new Camera Link assembly is capable of transmitting power directly to the camera from a PC framegrabber while transmitting exceptional Camera Link signals, eliminating the need for a separate power supply at the camera.

The POCL marked overmold ensures that POCL will not be confused with a standard Camera Link assembly in the field.

The mini CL interface offers the same performance of standard CL in a compact size. Combined with a high flex cable and durable overmolding, this offers the most versatile and robust Camera Link assembly.



Main Product Specifications

Features

- POCL marked Overmolding for easy identification
- Durable High Flex Cable
- Thumbscrew Locking
- 360 degree shielding
- RoHS Compliant

Cable Specifications	
Overall Diameter	.385 Inches
Max Temperature	80 Degrees C
Jacket Color	Black
UL/CSA Rated	20276 AWM I/II
Min. Bend Radius	3.85 Inches
Flame Rating	FT-1

Primary Components	
Cable	11 Individually Shielded Twisted Pairs
Connector A	26 Pos MDR
Connector B	26 Pos MDR

Ordering Information

Order Number	Description
POMCLP-xx-MP	Industrial Power Over Mini CL

Replace xx with length in meters
 For cables longer than 10 meters contact customer service

