

# Gig E Vision

## Industrial High Flex Gig E Assemblies - F-GEVP-xx-P

### Product Outline

Industrial High Flex Gig E cables are designed to interface Gig E and Gig E Vision cameras directly to a computer, eliminating the need for frame grabbers.

F-GEVP is the solution for brutal applications that require more than the traditional CAT 5 cable can offer. Double shielded cable ensures the best electrical performance. Our unique overmold design provides increased strain relief.

The high flex cable is designed to withstand 12 million + flex cycles. The durable TPE jacket provides additional protection from elements such as water, oil, and abrasion.



### Main Product Specifications

#### Features

- Overmolded strain relief
- High flex cable
- Robust TPE jacket
- Double shielded
- RoHS Compliant

#### Cable Specifications

Overall Diameter	.245 Inches
Max Temperature	80 Degrees C
Jacket Color	Black
UL/CSA Rated	Yes
Min. Bend Radius	2.45 Inches
Flame Rating	FT-1

#### Primary Components

Cable	4 Twisted Pairs
Connector A	Standard RJ45
Connector B	Standard RJ45

### Ordering Information

Order Number	Description
F-GEVP-xx-P	High Flex Gig E

Replace xx with length in meters

Custom variations available. Please contact customer service for additional information.



Pyramid Imaging

[www.PyramidImaging.com](http://www.PyramidImaging.com) • [Sales@PyramidImaging.com](mailto:Sales@PyramidImaging.com)

Phone: 813-984-0125 • Fax: 866-874-9521