LXG.P Starter Kit

Article number: 11165156

overview

- dual port GigE PCle x4 interface board with PoE support
- GigE cables 3,0 m
- 2x trigger/flash cable, 5,0 m
- power supply kit for LX, PX and VCXG cameras
- Mounting Adapter Type B (Tripod)
- Software (WINDOWS) via Download
- camera not included





945 East 11th Avenue Tampa, FL 33605

Phone: (813) 984-0125

Contact: Sales@ pyramidimaging.com

https://pyramidimaging.com

technical data	
fixing	
article number	11003060
name	Mounting Adapter Type B (Tripod)
features	 easy camera mounting robust anodized surface stable lightweight metal design (aluminium, 17g) UNC ¼"- 20 thread for mounting (tripod thread)
cable	
article number	10170048
name	cable GigE RJ45/RJ45, 3,0 m
features	GigE cableRJ45/RJ45CAT7length 3,0 m
process interface cable	
article number	11004523
name	cable 8 wires, 5,0 m (ESG 32FH0500)
features	 cable M8 female connector 8-pin open wires at one side cable carrier compatible length 5,0 m
article number	11118799
name	cable 8 wires, 5,0 m (Z-KSG 32FP0500G)

process interface cable	
features	 shielde cable M8 male connector 8 pole open wires at one side cable carrier compatible length 5,0 m
interface card	
article number	11168453
name	PCI-1672PC Dual PoE (ZVA-PCIe- 1672PC)
features	 2 port GigE to PCI Express host adapter RJ45 connector chipset: Intel[®] I350-AM2 Power over Ethernet, IEEE 802.3af compliant, support class 0, 1, 2, 3, and 4, provides up to 15,4 Watt tested Jumbo Frames: 9 kByte Note: 4 lane PCI Express connector required
power supply	
article number	11122415
name	Power Supply Kit LX PX VCXG int.
features	 power supply 12V/2,0A international with adapters for EU, US, UK, AU, KR and power supply and process interface adapter cable for LX, PX and VCXG cameras length 5,0 m