



| 2/3" 1.8/12mm C | | 1/2" | 1/3" |
|---------------------------|------------|---------------------------------|-----------------|
| FOCAL LENGTH | | f=12mm | |
| MAX. DIAMETER (RATIO) | | F=1:1.8~11 | |
| ELEMENT | | 7 ELEMENTS 9 GROUPS | |
| PICTURE SIZE | | 6.6x8.8mm | 4.8x6.4 3.6x4.8 |
| ANGLE | VER. ANGLE | 29.8° | 21.9° 16.5 |
| | HOR. ANGLE | 39.1° | 28.9° 21.9° |
| | DIA. ANGLE | 47.8° | 35.8° 27.2° |
| DISTORTION (TV) | | -0.12% | - - |
| SHOOTING RANGE AT | VER. | 60.2mm | 43.7mm 32.7mm |
| MINIMUM FOCUS | HOR. | 80.7mm | 58.4mm 43.7mm |
| DISTANCE | DIA. | 101.5mm | 73.2mm 54.7mm |
| MINIMUM FOCUS DISTANCE | | 0.1m | |
| FLANGE BACK | | 17.526mm in air | |
| BACK FOCUS | | 13.9mm in air | |
| FILTER SCREW SIZE | | M25.5x0.5 | |
| FRONT/REAR EFFECTIVE DIA. | | FRONT 18.4mm | REAR 16.1mm |
| MOUNT | | C-MOUNT | |
| EXIT PUPIL | | 154.1 | |
| TEMPERATURE RANGE | | -10~+50°C | |
| STORAGE TEMPERATURE RANGE | | -20~+60°C | |
| RESOLUTION CENTER/CORNER | | CENTER 200lp/mm CORNER 160lp/mm | |
| LENS COATING | | WIDE BAND MULTI COATING | |
| WEIGHT | | 105 g | |

| | | | | |
|----------|-------|----------------------|-------|------|
| | | 尺度 1/1 | 承認 八木 | 製 富永 |
| | | 機種名 2/3" F1.8 f=12mm | | |
| | | 機種番 1-19554 | | |
| 09.09.01 | 作成年月日 | | | |