

overview

- Camera Link PCI Express x4 interface board, color calculation in HW
- power supply cable 5,0 m
- trigger/flash cable, 5,0 m
- Camera Link cable MDR/MDR 5,0 m (2 pieces)
- international power supply 12V/2,0A, cable length 1,8 m
- Software (Windows) via Download
- camera not included



technical data

cable

article number	11046254
name	2x cable mini CL MDR/SDR 5,0 m
features	<ul style="list-style-type: none"> • Camera Link® interface cable with MDR and SDR connectors to connect a Camera Link® camera to a framegrabber • length 5,0 m

process interface cable

article number	11004523
name	cable 8 wires, 5,0 m (ESG 32FH0500)
features	<ul style="list-style-type: none"> • cable • M8 female connector • 8-pin • open wires at one side • cable carrier compatible • length 5,0 m

interface card

article number	11014581
name	PCIe-CL microEnable IV AD4-CL
features	<ul style="list-style-type: none"> • Base, Dual Base, Medium and Full configurations support • quad lane PCI Express interface • 2 x MDR26 interface • 256 MB image buffer

power supply

article number	11044200
name	power supply 12V/2,0A intern.
features	<ul style="list-style-type: none"> • international power supply 12V/2.0A with M8/3-pin female connector • length 1,8 m • adapter for EU, US, UK, AU and KR

power cable

article number	10125607
name	shielded cable 3 wires, 5,0 m
features	<ul style="list-style-type: none"> • shielded cable • M8 female connector • 3-pin • open wires at one side • cable carrier compatible • length 5,0 m



Pyramid Imaging Inc
945 East 11th Avenue
Tampa, FL 33605
<https://pyramidimaging.com>
Sales@pyramidimaging.com
(813) 984-0125