

3 Mega Pixel lens

Tele-Xenar 2.2/70

In accordance with the sensitivity of modern 2 / 3" CCD and CMOS sensors, the 3 megapixel lenses are corrected and broadband-coated for the spectral range of 400 – 1000 nm (VIS + NIR). Even under production and / or extreme conditions, the robust mechanical design with lockable focus and iris setting mechanism guarantees reliable continuous use in which the set optical parameters remain in place.



Tele-Xenar 2.2/70

Key Features

- High-resolution optics
- Highest optical imaging performance even with smallest pixel sizes
- Broadband coating (400 - 1000 nm)
- Compact and low weight
- Vibration insensitivity for stable imaging performance
- Focus and iris setting lockable

Applications

- Machine Vision and other imaging applications
- 3D measurement
- Traffic
- Medical
- Robot vision
- Food processing

Technical Specifications



F-number	2.2
Focal length	70.5 mm
Image circle	11 mm
Transmission	400 - 1000 nm
Interface	C-Mount
Weight	200 gr.
Option	Optical filter

Contact

Jos. Schneider Optische Werke GmbH
 Ringstraße 132
 55543 Bad Kreuznach
 Germany
 Phone +49 671 601-387
 Fax +49 671 601-286
www.schneiderkreuznach.com/industrialoptics
industrie@schneiderkreuznach.com

Schneider Asia Pacific Ltd.
 20/F Central Tower, 28 Queen's Road
 Central, Hong Kong
 China
 Phone +852 8302 0301
 Fax +852 8302 4722
www.schneider-asiapacific.com
info@schneider-asiapacific.com

Schneider Optics Inc.
 285 Oser Ave.
 Hauppauge, NY 11788
 USA
 Phone +1 631 761-5000
 Fax +1 631 761-5090
www.schneideroptics.com/industrial
industrial@schneideroptics.com



TXR 2.2/70


f'	= 70.5 mm	β_p'	= 0.494
s_F	= -27.8 mm	s_{EP}	= 115.0 mm
$s_{F'}$	= 28.5 mm	$s_{A'P}$	= -6.3 mm
HH'	= -26.0 mm	Σd	= 58.8 mm

TXR 2.2/70

MODULATION with reference to the relative image height



Wavelength λ	[nm] :	555	655	605	505	455	405
Spectral weighting	[%] :	19.6	23.7	22.2	15.7	12.1	6.7
Spatial frequency R	[1/mm] :	10	20	30			
Format	[mm X mm] :	6.6	X	8.8			
Diagonal $2u'$	[mm] :	11.0					

radial —
tangential - - -




Focusing : MTF_{max} at f / 2.2 , R = 30 1/mm, u'/u'_{max} = 0

Tele-Xenar 2.2/70



TXR 2.2/70


$f' = 70.5 \text{ mm}$ $\beta_p = 0.494$
 $s_F = -27.8 \text{ mm}$ $s_{EP} = 115.0 \text{ mm}$
 $s_{F'} = 28.5 \text{ mm}$ $s_{AP} = -6.3 \text{ mm}$
 $HH' = -26.0 \text{ mm}$ $\Sigma d = 58.8 \text{ mm}$



RELATIVE ILLUMINATION

The relative illumination is shown for the given focal distances or magnifications.


	$f / 2.2$	$f / 4.0$	$f / 8.0$
—	$\beta' = -0.0200$	$u_{max}' = 5.5$	$00' = 3642.$
- -	$\beta' = -0.0500$	$u_{max}' = 5.5$	$00' = 1529.$
----	$\beta' = -0.1000$	$u_{max}' = 5.5$	$00' = 827.$



DISTORTION

Distortion is shown for the given focal distances or magnifications. Positive values indicate pincushion distortion and negative values barrel distortion.

—	$\beta' = -0.0200$	$u_{max}' = 5.5$	$00' = 3642.$
- -	$\beta' = -0.0500$	$u_{max}' = 5.5$	$00' = 1529.$
----	$\beta' = -0.1000$	$u_{max}' = 5.5$	$00' = 827.$



TRANSMITTANCE

Relative spectral transmittance is shown with reference to wavelength.



945 East 11th Avenue Tampa, FL 33605

Phone: (813) 984-0125

Contact: Sales@pyramidimaging.com

<https://pyramidimaging.com>