



945 East 11th Avenue Tampa, FL 33605

Phone: (813) 984-0125

Contact: Sales@ pyramidimaging.com

<https://pyramidimaging.com>

GIG VISION **GEN<i>i</i>CAM**



sensor information

sensor	Sony ICX274
resolution	1624 × 1236 px
exposure time	0,004 ... 60000 ms
pixel size	4.4 × 4.4 μm
shutter type	Global shutter
sensor type	1/1.8" CCD

acquisition formats

image formats, interface	Full Frame, 1624 × 1236 px, max. 16 fps
frame rate max.	Full Frame HQ, 1624 × 1236 px, max. 12 fps
	Binning 2×2 HQ, 812 × 618 px, max. 24 fps
	Binning 2×2, 812 × 618 px, max. 49 fps
	Binning 1×2 HQ, 1624 × 618 px, max. 24 fps
	Binning 1×2, 1624 × 618 px, max. 49 fps
	Full Frame HQ, 1624 × 1236 px, max. 12 fps
	Binning 2×1, 812 × 1236 px, max. 25 fps
pixel formats	Mono8
	Mono12
	Mono12 Packed

image preprocessing

analog controls	Gain (0 ... 20 dB)
	Offset (0 ... 255 LSB 12 Bit)

color models	Mono
--------------	------

interfaces and connectors

data interface	Gigabit Ethernet, Transfer rate 1000 Mbits/sec, Connector: 8P8C Modular Jack (RJ45), screwable type
process interface	M8 / 4 pins
power supply	M8 / 3 pins

mechanical data

lens mount	C-mount
width	36 mm
height	36 mm
depth	48 mm

mechanical data

weight	≤ 90 g
material	housing: aluminum

electrical data

voltage supply range +Vs	8 ... 30 V DC
power consumption	approx. 4,0 W

environmental conditions

operating temperature	+5 ... +50 °C
humidity	10 ... 90 % (non-condensing)
protection class	IP 40

conformity

conformity	CE
	RoHS
	FCC
	UL
	EAC

dimension drawing

