



945 East 11th Avenue Tampa, FL 33605

Phone: (813) 984-0125

Contact: Sales@pyramidimaging.com

<https://pyramidimaging.com>

GIG VISION **GEN<i>i</i>CAM**



sensor information

sensor	Sony ICX204
resolution	1032 × 776 px
exposure time	0,004 ... 60000 ms
pixel size	4.65 × 4.65 μm
shutter type	Global shutter
sensor type	1/3" CCD

acquisition formats

image formats, interface	Full Frame, 1032 × 776 px, max. 28 fps
frame rate max.	Full Frame HQ, 1032 × 776 px, max. 14 fps Binning 2×2 HQ, 516 × 388 px, max. 24 fps Binning 2×2, 516 × 388 px, max. 49 fps Binning 1×2 HQ, 1032 × 388 px, max. 24 fps Binning 1×2, 1032 × 388 px, max. 49 fps Binning 2×1 HQ, 516 × 776 px, max. 14 fps Binning 2×1, 516 × 776 px, max. 28 fps
pixel formats	Mono8 Mono12 Mono12 Packed

image preprocessing

analog controls	Gain (0 ... 20 dB) Offset (0 ... 255 LSB 12 Bit)
-----------------	---

color models	Mono
--------------	------

interfaces and connectors

data interface	Gigabit Ethernet, Transfer rate 1000 Mb/s/sec, Connector: 8P8C Modular Jack (RJ45), screwable type
process interface	M8 / 4 pins
power supply	M8 / 3 pins

mechanical data

lens mount	C-mount
width	36 mm
height	36 mm
depth	48 mm

mechanical data

weight	≤ 90 g
material	housing: aluminum

electrical data

voltage supply range +Vs	8 ... 30 V DC
power consumption	approx. 4,0 W

environmental conditions

operating temperature	+5 ... +50 °C
humidity	10 ... 90 % (non-condensing)
protection class	IP 40

conformity

conformity	CE RoHS FCC UL EAC
------------	--------------------------------

dimension drawing

