



COLOR DESIGNATION (RLD3-XXX)		
-XXX	COLOR	SPECTRUM
395	UV	395nm
470	BLUE	470nm
530	GREEN	530nm
630	RED	630nm
850	INFRARED	850nm
WHI	WHITE	WHITE

STANDARD M12, 5 PIN (MALE)		
PIN	SIGNAL	COLOR
1	+24VDC / 500mA MAX	BROWN
2	NPN STROBE	WHITE
3	GROUND	BLUE
4	PNP STROBE	BLACK
5	0-10 VDC ANALOG	GREEN

CONTINUOUS OPERATION: CONNECT EITHER PNP STROBE TO +24 VDC OR NPN STROBE TO GROUND.
 ANALOG SIGNAL: 0 VDC EQUALS 100% INTENSITY 10 VDC EQUALS 0% INTENSITY.

Spectrum Illumination	
5114 INDUSTRIAL PARK DR. MONTAGUE, MI 49437	
DRAWN BY: DDM	DATE: 6/25/06
SCALE: HALF	REV. LEVEL: B
DETAIL NAME: COMPLETE ASSEMBLY	
PROJECT NAME: RLD3 RING LIGHT	



Pyramid Imaging Inc
 945 East 11th Avenue
 Tampa, FL 33605
<https://pyramidimaging.com>
 Sales@pyramidimaging.com
 (813) 984-0125