

Monster Back Light 4"x8" Series



ELECTRICAL:

Input Voltage: See LDM 2800 spec Input Current: See LDM 2800 spec Connector: Quick Connect, 5 pin Reverse Key Euro / Micro

WARNING !!!

Use Only Spectrum Illumination LDM Driver with Monster Lights. Do Not Connect Monster Lights Directly to 24VDC!

MECHANICAL:

Driver: DIN Rail Mount Dimensions: http://www.spectrumillumination.com

ILLUMINATION:

Light Source: LED – 4 Colors Quantity HB LED's: 32 Light Emitting Pattern: 4" x 8" / 101mm x 203mm LED Life: up to 50,000 hours*. *Contact us for LED life information

DIFFUSERS:

Polarizer – Option /P

PART NUMBER DESIGNATION:

MBL48-XXX

XXX = Light Color -470, -530, -630 & -WHI

		λ	λ	Spectral		
		Dominant	Dominant	Half-width	λ Peak	
Color	Dash #	Typical	Range	Δλ1/2	Typical	Units
Red	-630	625	620 - 632	18	632	nm
Green	-530	528	513 - 537	33	520	nm
Blue	-470	470	464 - 476	25	465	nm
White	-WHI	Color Temp 5600K typical				

Light includes LDM DIN rail mount constant current driver, 4-meter cable (driver is available with variable or 0-10VDC intensity control - cable also available in 8, 15 and 30-meter lengths).



Pyramid Imaging Inc 945 East 11th Avenue Tampa, FL 33605 https://pyramidimaging.com Sales@pyramidimaging.com (813) 984-0125