



2/3" 1.4/16mm C		1/2"	1/3"
FOCAL LENGTH		f=16mm	
MAX. DIAMETER (RATIO)		F=1:1.4,4,8,16	
ELEMENT		7群 8枚	
PICTURE SIZE		6.6x8.8mm	4.8x6.4
ANGLE	VER. ANGLE	22.7°	16.4°
	HOR. ANGLE	30.0°	21.8°
	DIA. ANGLE	37.0°	27.0°
DISTORTION (TV)		-0.05%	-
SHOOTING RANGE AT	VER.	84.4mm	61.2
	HOR.	112.8mm	81.8
	DIA.	141.2mm	102.5
MINIMUM FOCUS DISTANCE		0.2m	
FLANGE BACK		17.526 mm in air	
BACK FOCUS		13.1mm in air (Mechanical 13.1mm in air)	
FILTER SCREW SIZE		M27x0.5	
FRONT/REAR EFFECTIVE DIA.		FRONT φ20.2mm	REAR φ15.5mm
MOUNT		C-MOUNT	
EXIT PUPIL		340mm	
TEMPERATURE RANGE		-10~+50°C	
STORAGE TEMPERATURE RANGE		-20~+60°C	
RESOLUTION CENTER/CORNER		中心100本/mm / 周辺 80本/mm	
WEIGHT		g	

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



		尺度 1/1	承認 八木	製図 八木
		機種名 2/3" F1.4 f=16mm		
2014.2.24	作成年月日	LM16JCM-V		