



945 East 11th Avenue Tampa, FL 33605
 Phone: (813) 984-0125
 Contact: Sales@pyramidimaging.com
<https://pyramidimaging.com>

2/3" F2/35mm C		1/2"	1/3"
FOCAL LENGTH		f=35mm	
MAX. DIAMETER (RATIO)		F=1:2,4,8,16	
ELEMENT		4群 7枚	
PICTURE SIZE		6.6x8.8mm	3.6x4.8
ANGLE	VER. ANGLE	10.8°	5.89°
	HOR. ANGLE	14.4°	7.85°
	DIA. ANGLE	17.9°	9.81°
DISTORTION (TV)		-0.2%	-0.05%
SHOOTING RANGE AT	VER.	35.8mm	19.5
MINIMUM FOCUS	HOR.	47.9mm	26.0
DISTANCE	DIA.	60.0mm	32.5
MINIMUM FOCUS DISTANCE		0.2m	
FLANGE BACK		17.526 mm in air	
BACK FOCUS		20.1mm in air (Mechanical 14.0mm in air)	
FILTER SCREW SIZE		M27.0x0.5	
FRONT/REAR EFFECTIVE DIA.		前φ21.5mm	後φ11.7mm
MOUNT		C-MOUNT	
EXIT PUPIL		-38.7	
TEMPERATURE RANGE		-10~+50°C	
STORAGE TEMPERATURE RANGE		-20~+60°C	
RESOLUTION CENTER/CORNER		中心100本/mm	周辺 80本/mm
WEIGHT		g	

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



		尺度 1/1	承認 八木	製図 八木
		機種名	2/3" F2 35mm	
2014.2.24	作成年月日	LM35JCM-V		