



945 East 11<sup>th</sup> Avenue Tampa, FL 33605

Phone: (813) 984-0125

Contact: Sales@pyramidimaging.com

<https://pyramidimaging.com>

## Image Processing and Analysis Library

$$\nabla^2 f(x,y) \equiv \frac{\partial^2 f}{\partial x^2} + \frac{\partial^2 f}{\partial y^2} \quad \frac{d_2 - f}{f}$$

```
for(;;) {
  capture();
  difference();
  lowpass();
  if (findblobs())
    reportlargest();
}
```

$$\begin{bmatrix} \cos\theta & \sin\theta & 0 \\ -\sin\theta & \cos\theta & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

**Pixel Clock:** 45MHz  
**Pixel Jitter:** 1.0 ns  
**Resolution:** 6144 x 4096  
**Buffers:** 253  
**Pixel Bits:** 8  
**Camera:** Area Scan  
**Trigger:** TTL  
**Field Delay:** 5

$$\frac{1}{d_1} + \frac{1}{d_2} = \frac{1}{f}$$

**Blobs Found:** 259  $\frac{2\lambda}{\pi n \Omega_0}$   
**Center of Mass:** (23.65, 78.78)  
**Subpixel Edge @:** (97.3498, 87.5000)

$$\delta = 1.22 \frac{\lambda d_i}{l} \quad s.n.r. = \frac{\bar{x}}{\sqrt{\sum (x_i - \bar{x})^2 / n}}$$

### FEATURES

- Image Processing and Analysis.
- Image Graphics and Printing.
- Image Morphology and Transforms.
- Subpixel Accuracy Measurements.
- Blob Analysis and Particle Tracking.
- Image Correlation.
- Image Load, Save, and Print.
- For use with XCLIB, SVOBJ, or 4MOBJ.
- C/C++ Library for 16 & 32 Bit DOS Programs.
- DLL for 16, 32, 64 bit Windows Applications.
- C/C++ Library for 32 bit & 64 bit Linux Programs.

### PROCESSING POWER

The PXIPL Library empowers C/C++ and Windows programmers to process and analyze images in conjunction with:

- The PIXCI® imaging boards and XCLIB Library,
- The EPIX® SILICON VIDEO® cameras, their PIXCI® imaging board, and XCLIB Library,
- The 4MEG VIDEO™ imaging boards and 4MOBJ Library, or
- The SV-MUX™ imaging boards and SVOBJ Library.

The PXIPL Library is compatible with all of the hardware and software environments supported by the XCLIB, 4MOBJ, and SVOBJ libraries. PXIPL routines operate directly upon imaging board buffers, upon images in PC memory, or upon images stored on disk.

PXIPL provides a wide selection of imaging routines. The major categories include: processing, enhancements, graphic lines and shapes, text overlay, printing, morphology, filters and edge detectors, transforms, convolutions, sequence integration and averaging, image printing, image copy and resizing, single image and image pair normalizations, blob analysis, histograms and moments, image load and save, calibration, correlation, subpixel accuracy measurements, and particle tracking.

### SOPHISTICATED SOLUTIONS

The PXIPL C/C++ Function Library allows embedding image processing and analysis into user-written applications. Under Windows, the PXIPL DLL provides services to existing Windows applications which support "hooks" into DLLs.

Under Windows, PXIPL also provides image display on the SVGA with integrated (non-blinking) cross-hair cursor overlay and integrated palette modifications. PXIPL also provides "waterfall" display of repeatedly captured image lines on the SVGA.

PXIPL assists user-written programs in applications such as image enhancement, archival, analysis, and measurement; event and motion study; document capture; particle analysis; visual inspection; machine vision and quality control. Join the scientists and engineers in medical, industrial, and research environments who rely upon EPIX® imaging solutions.

### FEATURES

**Resolution Flexibility** - PXIPL functions can process images of almost any size, located either in image board memory, PC memory, or disk files.

PXIPL functions will process any image captured by an EPIX® imaging board using either 4MOBJ, SVOBJ, or XCLIB software. Typical capture resolutions include 4x1, 32x32, 512x240, 752x480, 768x580, 1024x768, or 2048x2048. Monochrome pixels with a dynamic range from 1 bit (2 grey levels) to as large as 16 bits ( $2^{16}$  grey levels) can be processed. Color pixels, in either RGB, YCrCb, or HSB color space, with a range of 1 to 16 bits per color component, are supported. Selected operations also support up to 32 bits per pixel. Image sequence operations, such as sequence average or sequence integration, support up to  $2^{23}$  images (8 bits per pixel).

The PXIPL functions are not restricted to processing images which were captured by EPIX® imaging boards. Images from any source, residing in PC memory, can be any size and any number of colors, limited only by availability of PC memory, and the CPU word size.<sup>1</sup>

**Virtual Memory** - Should PC memory be insufficient, images may also reside in disk files. All images, whether in an imaging board buffer, in PC memory, or in a disk file, can be enhanced and analyzed by the same functions!

**Functional Flexibility** - Typical PXIPL functions provide a broad spectrum of operations, allowing a single function to do the work of many functions. For example, a convolution function accepts parameters describing the image buffer, the area of interest within the buffer, the convolution size  $N$ , and the  $N \times N$  kernel coefficients. This single function allows convolving with a 3x3, 9x9, 31x31, or 99x99 kernel size, limited only by available PC memory.

**Efficiency** - PXIPL functions are coded in optimized C, with selected segments hand-coded in assembler. Many functions internally identify special cases, invoking code optimized for each special case. The  $N \times N$  convolution, for example, examines the coefficients provided and selects custom routines depending upon the size of  $N$ , the multiplication and summation precision needed, and whether division is required.

**Proven Performance** - The same functions provided with PXIPL also form the backbone of the ready-to-run XCAP, 4MIP, SVIP, and XCIP interactive image analysis programs, and have been proven through daily use in on-line, rigorous, imaging applications.

**Image Selection Flexibility** - A typical enhancement function operates on any image buffer, on either the full image or selected area of interest, with the result saved to any buffer or area of interest of the same dimensions. Image pair operations allow independent selection of the two source image operands and of the image destination.

PXIPL functions for nonrectangular regions use a common method of region specification, supporting rotated elliptical, rotated rectangular, N-sided polygon, boundary path, and scan list specifications.

Functions can operate on any pixel color component of a color image; selected functions can also operate upon all color components.

```

struct pximage im1, im2, im3;
struct pxy      xysize = {752, 480};
unsigned char  buffer[752][480];
void           *mallocbuf = NULL;

im1 = *pxd_defineImage(1,1, // access imaging
                      0,0,-1,-1,...,"Grey"); // board's buffer 1.

pximage_memory(&im, buffer, // access existing
               &xysize, PXDATUCHAR, // image in PC malloc memory,
               8, 1, // size 752x480, of chars,
               PXHINTGREY, 0); // 8 bits per pixel,
                               // one color, monochrome

pximage_memmalloc(&im3, // create & access new image
                 &mallocbuf, &xysize, // in PC memory, 752x480,
                 PXDATUCHAR, 8, // of chars, 8 bits/pixel,
                 1, PXHINTGREY); // one color, monochrome

pxip8_pairsub(&im1, &im2, // Subtract pixels of
              &im3, 0); // image 1 from image 2,
                       // put result in image 3.

struct pximage *ip1, *ip2, *ip3;
unsigned long  histogram[16], cnt;

ip1 = pxd_defineImage(1,1, // access image board buffer 1,
                      188,120,564,360, // AOI of center 1/4 (assuming
                      ..., "BofRGB"); // 752x480), RGB color space,
                      // access color #3, B of RGB.

pxip8_histab2(NULL, ip1, // compute Blue AOI histogram
              histogram,16); // binned into 16 ranges.

ip2 = pxd_defineImage(1,1, // access image board buffer 1,
                      0,0,-1,-1,..., // full image AOI, as HSB,
                      "SofBSH"); // access color #2, S of HSB.

pxip8_pixthresholdcnt(NULL, // count Saturation
                      ip2, 42, 0,&cnt); // values >= 42

ip3 = pxd_defineImage(1,2, // access image board buffer 2,
                      0,0,-1,-1,..., // full image AOI, as HSB
                      "SofBSH"); // access color #2, S of HSB

pxip8_copy(NULL, &ip3, &ip2); // set saturation of buffer 1
                              // from buffer 2, leaving
                              // hue & brightness unchanged
    
```

Operating upon imaging board buffers & images in PC memory.    Operating upon selected colors of selected color space.

### FEATURES

### PXIPL FUNCTIONS

Add Pixels of Image Pair  
 Add Pseudo-Random Noise  
 AND Pixels of Image Pair  
 AND Pixels with Mask in Region  
 AND Pixels with Mask  
 Average Image Sequence  
 Average Pixels of Image Pair  
 AVI 1.0 File, Save Image Sequence  
 AVI 1.0 File, Save Image Sequence  
 AVI 1.0 File, Save Sequence - Init  
 AVI 2.0 File, Save Image Sequence  
 AVI 2.0 File, Save Sequence - Init  
 AVI File, Load Image Sequence  
 AVI x.0 File, Save Sequence - Add Image  
 AVI x.0 File, Save Sequence - Done  
 Binary File, Save Sequence - Add Image  
 Binary File, Save Sequence - Done  
 Binary File, Save Sequence - Init  
 Blend Pixels of Image Pair  
 BMP File, Load Image  
 BMP File, Save Image  
 Calibrate Intensity/Density Mapping  
 Calibrate Spatial Mapping  
 Complement Pixel Values in Region  
 Complement Pixel Values  
 Compress Region Path  
 Compute Center of Mass of Nth Power of Region  
 Compute Center of Mass of Nth Power  
 Compute Center of Mass of Region  
 Compute Center of Mass  
 Compute Center of Mass, Binary Image Region  
 Compute Center of Mass, Binary Image  
 Compute Histogram on Region  
 Compute Histogram on Region  
 Compute Histogram on Region  
 Compute Histogram Statistics w. Interpretation  
 Compute Histogram Statistics  
 Compute Histogram Statistics  
 Compute Histogram Statistics  
 Compute Histogram  
 Compute Moments of Region w. Interpretation  
 Compute Moments of Region  
 Compute Moments w. Interpretation  
 Compute Moments  
 Compute Radial Mass w. Interpretation  
 Compute Radial Mass  
 Compute Shape Statistics of Image Region  
 Compute Tabulated Histogram of Differences on Region  
 Compute Tabulated Histogram of Differences  
 Compute Tabulated Histogram  
 Compute Tabulated Histogram  
 Construct PXIMAGE: 3-D Slice of 3-D Image  
 Construct PXIMAGE: 3-D Representation of 2-D Image  
 Construct PXIMAGE: Access Freq. Domain Complex Image  
 Construct PXIMAGE: Access Image in File  
 Construct PXIMAGE: Access Image in File, Done  
 Construct PXIMAGE: Access Image in Host Memory  
 Construct PXIMAGE: Access Image in Host Memory  
 Construct PXIMAGE: Access Image in Host Memory  
 Construct PXIMAGE: Access Imaging Board Buffer  
 Construct PXIMAGE: Access Imaging Board Buffer  
 Construct PXIMAGE: Allocate Image in Malloc'ed Memory  
 Construct PXIMAGE: Allocate Image in Malloc'ed Memory  
 Construct PXIMAGE: Converted Color Space of Image  
 Construct PXIMAGE: Release Image in Malloc'ed Memory  
 Construct PXIMAGE: Release Image in Malloc'ed Memory  
 Construct PXIMAGE: Slice of Color Image  
 Construct PXIMAGE3: Access Image Sequence in Host Memory  
 Construct PXIMAGE3: Access Image Sequence in Host Memory  
 Construct PXIMAGE3: Access Imaging Board Buffers  
 Construct PXIMAGE3: Access Imaging Board Buffers  
 Construct PXIMAGE3: Access Imaging Board Buffers  
 Construct PXIMAGE3: Access Imaging Board Buffers  
 Construct PXIMAGE3: Access Imaging Board Buffers  
 Construct PXIMAGE3: Access Imaging Board Buffers  
 Construct PXIMAGE3: Access Imaging Board Buffers  
 Construct PXIMAGE3: Release Access to Imaging Board Frame Buffers  
 Construct PXIMAGE3: Release Access to Imaging Board Frame Buffers  
 H-P PCL Font: Draw Line of Characters  
 H-P PCL Font: Load  
 H-P PCL Font: Obtain Character Info  
 H-P PCL Font: Obtain Information  
 H-P PCL Font: Unload  
 HalfTone by Black/White Sum  
 Histogram Equalization  
 Image File, Obtain Information on Subfiles  
 Image File, Obtain Information  
 Image File, Release Information  
 Import Region from File  
 Initialize Region Path  
 Insert of Differences of Image Pair  
 Integrate Image Sequence  
 JPEG File, Load Image  
 JPEG File, Save Image  
 Left Shift Pixel Values in Region  
 Left Shift Pixel Values  
 Line Pair Pixel Shuffle  
 Line Pair Pixel UnShuffle  
 Linux: Display Cursor via XWindows/X11  
 Linux: Display Image via XWindows/X11  
 Load Image from File, Hex ASCII  
 Load Image from File, Packed Binary  
 Load Image from File, Unpacked Binary  
 Load Image Sequence from File, Packed Binary  
 Load Image Sequence from File, Unpacked Binary  
 Map Pixel Values in Region  
 Map Pixel Values  
 Map Uchar Pixel Values in Region  
 Map Uchar Pixel Values  
 Map uint16 Pixel Values in Region  
 Map uint16 Pixel Values  
 Map uint32 Pixel Values in Region  
 Map uint32 Pixel Values  
 Maximum of Pixels of Image Pair  
 Medial Axis Thinning  
 Minimum of Pixels of Image Pair  
 DOS Mouse: Get Clicks  
 DOS Mouse: Get Motion  
 DOS Mouse: Get Status  
 DOS Mouse: Get Status  
 DOS Mouse: Initialize Access  
 DOS Mouse: Terminate Access

DOS S/VGA: Set Mode and Initialize Access  
 DOS S/VGA: Terminate Access  
 Draw 2-D Cosine Product Pattern  
 Draw 2-D Fiducial Pattern  
 Draw 2-D Gaussian Pattern  
 Draw 2-D Separable Patterns  
 Draw Alignment Pattern  
 Draw Arrow  
 Draw Box  
 Draw Characters  
 Draw Curved Line defined as Bezier Polynomial  
 Draw Ellipse  
 Draw Icon or Cursor  
 Draw Icon Primitive, Free Resources  
 Draw Icon Primitive, Initialize  
 Draw Icon Primitive, Modify Pixels  
 Draw Icon Primitive, Test Completion  
 Draw Line Segment  
 Draw Region Boundary  
 Draw Region Path  
 Draw Test Pattern  
 Draw Text from Font Map  
 Draw Text  
 Edge Detection, Kirsch  
 Edge Detection, Roberts  
 Edge Detection, Sobel Absolute  
 Edge Detection, Sobel  
 Edge Gradient, Thin  
 Ellipse Fitting Measurement  
 Errors: Translate Error Code to String  
 Exclusive OR Pixels of Image Pair  
 Export Region to File  
 Extend Region Path  
 Extend Region Path  
 FFT: Filter Frequency Domain  
 FFT: Get Dimensions of Freq. Domain Representation  
 FFT: Inverse Transform Image  
 FFT: Log Magnitude Plot of Freq. Domain  
 FFT: Scale Freq. Domain by Log Magnitude Plot  
 FFT: Transform Image  
 Field Interlaced Image Line Shuffle  
 Field Interlaced Image Line UnShuffle  
 FIFO Average  
 Filter, Low Pass, Fixed  
 Filter, Low Pass, Low Smear  
 Filter, Low Pass, Weighted  
 Filter, Median  
 Filter, Median, Binary Images  
 Filter, Median, Weighted  
 Filter, Rank High (Dilate)  
 Filter, Rank Low (Erode)  
 Filter, Thicken, Laxiscian  
 Find Blobs and List  
 Find Blobs and List  
 Find Blobs, Analyze and List  
 Find Region's Enclosed Area  
 Find Region's Enclosing Window  
 FITS File, Load Image  
 FITS File, Save Image  
 Follow and Collect Region Boundary by Value  
 Free Region  
 Gamma Correction  
 Get PXIMAGE: Access Imaging Board Buffer  
 Get PXIMAGE: Access Imaging Board Color Buffer  
 Get PXIMAGE: Access Imaging Board Frame Buffer  
 Get PXIMAGE: Access Imaging Board Frame Buffer  
 Get PXIMAGE3: Access Access to Imaging Board Frame Buffers  
 Get PXIMAGE3: Access Imaging Board Buffers  
 Get PXIMAGE3: Access Imaging Board Color Buffers  
 Get PXIMAGE3: Access Imaging Board Frame Buffers  
 Get PXIMAGE3: Access Imaging Board Frame Buffers  
 Get PXIMAGE3: Release Access to Imaging Board Frame Buffers  
 H-P PCL Font: Draw Line of Characters  
 H-P PCL Font: Load  
 H-P PCL Font: Obtain Character Info  
 H-P PCL Font: Obtain Information  
 H-P PCL Font: Unload  
 HalfTone by Black/White Sum  
 Histogram Equalization  
 Image File, Obtain Information on Subfiles  
 Image File, Obtain Information  
 Image File, Release Information  
 Import Region from File  
 Initialize Region Path  
 Insert of Differences of Image Pair  
 Integrate Image Sequence  
 JPEG File, Load Image  
 JPEG File, Save Image  
 Left Shift Pixel Values in Region  
 Left Shift Pixel Values  
 Line Pair Pixel Shuffle  
 Line Pair Pixel UnShuffle  
 Linux: Display Cursor via XWindows/X11  
 Linux: Display Image via XWindows/X11  
 Load Image from File, Hex ASCII  
 Load Image from File, Packed Binary  
 Load Image from File, Unpacked Binary  
 Load Image Sequence from File, Packed Binary  
 Load Image Sequence from File, Unpacked Binary  
 Map Pixel Values in Region  
 Map Pixel Values  
 Map Uchar Pixel Values in Region  
 Map Uchar Pixel Values  
 Map uint16 Pixel Values in Region  
 Map uint16 Pixel Values  
 Map uint32 Pixel Values in Region  
 Map uint32 Pixel Values  
 Maximum of Pixels of Image Pair  
 Medial Axis Thinning  
 Minimum of Pixels of Image Pair  
 DOS Mouse: Get Clicks  
 DOS Mouse: Get Motion  
 DOS Mouse: Get Status  
 DOS Mouse: Get Status  
 DOS Mouse: Initialize Access  
 DOS Mouse: Terminate Access

Morphology Erosion  
 Morphology Hit-Miss  
 Morphology Open  
 MSB Extend Pixel Values in Region  
 MSB Extend Pixel Values  
 Normalize Columns Mean  
 Normalize Image as per Background Image  
 Normalize Lines Mean  
 NxN Convolution, Integer  
 NxN Convolution, Real  
 NxN Dynamic Threshold  
 NxN Inverse Contrast Ratio Mapping  
 Obtain Filtered pximage Access into Imaging Board Memory  
 Obtain Filtered pximage3 Access into Imaging Board Memory  
 Obtain pximage Access into Imaging Board Memory  
 Obtain pximage3 Access into Imaging Board Memory  
 Offset Pixel Values in Region  
 Offset Pixel Values in Region  
 Offset Pixel Values  
 Offset Pixel Values  
 OR Pixels of Image Pair  
 OR Pixels with Mask in Region  
 OR Pixels with Mask  
 Overlay Pixels of Image Pair  
 Overlay Pixels of Image Pair  
 Paint within Region  
 PCX File, Save Image  
 Perform Intensity/Density Mapping  
 Perform Inverse Spatial Mapping  
 Perform Spatial Mapping  
 Print Image  
 Product of Pixels of Image Pair  
 Product of Pixels of Image Pair  
 PXIMREGION: NonRectangular Image Region Specification  
 Ratio of Pixels of Image Pair  
 Ratio of Pixels of Image Pair  
 Recursive Average  
 Release Intensity/Density Mapping State  
 Release Spatial Mapping State  
 Right Shift Pixel Values in Region  
 Right Shift Pixel Values  
 S/VGA: Display Cursor  
 S/VGA: Display Image  
 S/VGA: Translate Image to Screen Coordinates  
 S/VGA: Translate Screen to Image Coordinates  
 S/VGA: Waterfall Line Display  
 Save Image Sequence to File, Packed Binary  
 Save Image Sequence to File, Unpacked Binary  
 Save Image to File, Hex ASCII  
 Save Image to File, Packed Binary  
 Save Image to File, Unpacked Binary  
 Scale Pixel Values in Region  
 Scale Pixel Values in Region  
 Scale Pixel Values  
 Scale Pixel Values  
 Scan, Connect, Collect Region by Table  
 Scan, Connect, Collect Region by Value  
 Search for Largest Pixel Value  
 Search for Pixel by Table  
 Search for Pixel by Value  
 Search for Smallest Pixel Value  
 Set Color Pixel Values in Region  
 Set Color Pixel Values  
 Set Pixel Components to Maximum in Region  
 Set Pixel Components to Maximum  
 Set Pixel Components to Median in Region  
 Set Pixel Components to Median  
 Set Pixel Components to Minimum in Region  
 Set Pixel Components to Minimum  
 Set Pixel Values in Region  
 Set Pixel Values  
 Set PXIMAGE: Set 2-D Area of Interest Window  
 Set PXIMAGE3: Set 3-D Area of Interest Window  
 Set Real Pixel Values  
 Shift Image One-Half Line Up or Down  
 Shuffle Column Order to Even-Odd Halves  
 Shuffle Even-Odd Halves to Column Order  
 Spatial Intensity Normalization  
 Spatial Quantization & Shrink  
 Subpixel Edge Measurement  
 Subtract Pixels of Image Pair  
 Swap Lines or Column Pairs  
 Targa File, Save Image  
 Threshold Pixel Values in Region  
 Threshold Pixel Values in Region  
 Threshold Pixel Values in Region  
 Threshold Pixel Values  
 Threshold Pixel Values  
 Threshold Pixel Values  
 TIFF File, Load Image Sequence  
 TIFF File, Load Image  
 TIFF File, Save Image Sequence  
 TIFF File, Save Image  
 TIFF File, Save Sequence - Add Image  
 TIFF File, Save Sequence - Done  
 TIFF File, Save Sequence - Init  
 Tile Image Sequence  
 Track Particle Motion  
 Translate Region Definition to Path  
 Translate Region Definition to Scan List  
 User-De-fined Premature Termination Functions  
 Windows: Create Device Independent Bitmap (DIB)  
 Windows: Display Cursor via GDI  
 Windows: Display Image via DirectDraw  
 Windows: Display Image via GDI  
 Windows: Display Image via Video for Windows  
 Windows: Draw Text using FONT  
 Windows: Release Device Independent Bitmap (DIB)  
 Windows: Translate Device to Image Coordinates  
 Windows: Translate Image to Device Coordinates  
 Windows: Waterfall Line Display via GDI  
 XOR Pixels with Mask in Region  
 XOR Pixels with Mask

## FEATURES

```
int kernel[15][15], i, j; // Define 15x15 kernel as low pass
for (i = 15; i--; ) // filter with all coefficients 1.
    for (j = 15; j--; )
        kernel[i][j] = 1;

pxip8_NxNconvolve( // Do 15x15 convolution on 100x100
    pxd_defineImage(1,1,0,0,100,100,...,"Grey"),
    // AOI of buffer 1, result into
    pxd_defineImage(1,2,0,0,100,100,...,"Grey"),
    15, kernel, 0, 0, 0); // buffer 2.
```

### Performing 15x15 convolution on AOI.

```
struct pxywindow bounds;
struct pxip8blob blob[100]; // results
struct pxy search = {-1, 0}; // init search coordinates
int n, i;
bounds.nw.x = 3; // min blob width
bounds.nw.y = 3; // min blob height
bounds.se.x = 100; // max blob width
bounds.se.y = 100; // max blob height
n = pxip8_bloblist(NULL, // search image buffer 5
    pxd_defineImage(1,5,0,0,-1,-1,...,"Grey"),
    &search, 'g'^'t', 123, 0, // for up to 10 blobs
    &bounds, 0, NULL, 100, blob, NULL); // identified by pixel
    // values >= 123

printf("Blobs found: %d\n", n);
for (i = 0; i < n; i++) // report blobs
    printf("Blob: %d, Center of Mass: (%g,%g), Area: %ld\n",
        i, blob[i].ucom.xd, blob[i].ucom.yd, blob[i].xyarea);
```

### Searching for blobs.

```
struct pxio8tiffparm tiffparm;
memset(&tiffparm, 0, sizeof tiffparm);
tiffparm.bits = 8; // set number of bits to be saved
tiffparm.description = "Test Run #4"; // and a short description.
for (int i = 0; i < 100; i++) // save sequence of 100 buffers
    pxio8_tiffwrite(NULL,
        pxd_defineImage(1,i+1,0,0,-1,-1,...,"Default"),
        "RUN4.TIF", i, // from image buffer i & full AOI
        NULL, &tiffparm, 0); // to file name & subimage number
```

### Saving image sequence to single TIFF file.

```
double mass, xcenter, ycenter;
pxip8_masscenter(NULL, // use AOI of buffer 3
    pxd_defineImage(1,3,0,0,100,100,...,"Grey"),
    &mass, &xcenter, &ycenter); // returned results
printf("Mass Center @ (%g,%g)\n",
    xcenter, ycenter); // report results
```

### Computing Center of Mass of AOI.

## SPECIFICATIONS

### IMAGING BOARD:

For use with XCLIB: Any PIXCI® A, CL1, CL2, CL3SD, D, D24, D32, D2X, D3X, E1, E1DB, E4, E4DB, EB1, EB1-PoCL, EC1, ECB1, ECB1-34, EL1, EL1DB, SI, SI1, SI4 SV2, SV3, SV4, SV5, SV5A, or SV5B imaging board. Any PIXCI® imaging board with an EPIX® SILICON VIDEO® camera.

For use with 4MOBJ: Any 4MEG VIDEO™ Model 5, Model 10, or Model 12, imaging board. Also supports the IMAGE MEMORY EXPANSION and the COC40 series<sup>2</sup> for use with the Model 12.

For use with SVOBJ: Any SILICON VIDEO® MUX™ imaging board.

### ENVIRONMENT:

Standard versions support:

- Microsoft C/C++ V7.0, V8.0 (Visual C/C++ V1/V2) 16 bit in M or L models. For DOS V3.0 or later, 8088 or better.
- Borland C/C++ V4.0, V5.0 16 bit in M or L models. For DOS V3.0 or later, 8088 or better.
- Watcom C/C++ V11.0 32 bit in F model. For Tenberry (Rational) DOS extender, 80386 or better.
- Windows 3.x 16 bit DLLs, for any compiler or Windows application. For Windows V3.x, Standard or Enhanced mode, 80286 or better.
- Windows 95, 98, ME 32 bit DLLs, for any compiler or Windows application.
- Windows NT, 2000, XP, Vista 32 bit DLLs, for any compiler or Windows application.
- Windows XP(x64), Vista(x64) 64 bit DLLs, for any compiler or Windows application.
- Linux V2.4.8 or later kernel on Intel 80x86.
- Linux V2.6 or later kernel on Intel x86-64.

Other environments available on request.

Memory requirements: Approximately 16 to 1024 Kbytes, dependent upon selection of library routines.

PXIPL is optionally provided with, and must be used with, the 4MOBJ, SVOBJ, XCLIB version with which it is packaged. PXIPL routines require the presence of a supported imaging board.

### LICENSING:

Licensing permits royalty free inclusion of library routines into programs using the 4MEG VIDEO™, the SILICON VIDEO® MUX™, or the PIXCI® imaging boards.

### SOFTWARE INCLUDES:

As required by chosen environment: Object code libraries (.lib), Dynamic Link Library (.dll), and/or Object code archive (.a).

C prototype files (.h).

Printed manual(s).



Pyramid Imaging

945 East 11th Avenue Tampa, FL 33605

sales@pyramidimaging.com

www.pyramidimaging.com

813-786-3785

1. In 16 bit programming environments: the product of the number of pixels per line and color components per pixel may not exceed 32767, the number of lines may not exceed 32767. In 16 and 32 programming environments: the size of an image and image sequence may not exceed 2<sup>32</sup>-1 bytes. In 64 programming environments: the size of an image may not exceed 2<sup>32</sup>-1 bytes, the size of an image sequence may not exceed 2<sup>64</sup>-1 bytes.

2. PXIPL for the COC40 supports Native and Bound routines for the TMS320C40, as well as PC routines. A detailed description is provided in the PXIPL-COC40 brochure.

The Waterfall Display feature requires digitization and field counts, and is intended only for use with imaging board buffers. Specifications subject to change without notice.

EPIX® imaging products are made in the USA.

EPIX, 4MEG VIDEO, COC40, SILICON VIDEO, SILICON VIDEO MUX, PIXCI, QUICK SET VIDEO, 4MOBJ, SVOBJ, XCLIB, XCOBJ, and PXIPL are trademarks or registered trademarks of EPIX, Inc. Other brand, product, and company names are trademarks or registered trademarks of their respective owners.

Copyright © 2009 EPIX, Inc. All rights reserved. 26-May-2009.